

Double Chamber Machine DK 1000

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- vacuum detection (no Time Controls)
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, arms
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Control panel LC

DK 1000 LS

Technical Data		DK 1000	Technical Data		DK 1000
■ Chamber size	height	200 mm	■ Weight	650 kg	
	depth	840 mm		■ Length of sealing bar	4 x 860 mm
	width	1005 mm	■ Packaging performance		1-3 / min.
■ External dimensions	height	1020 mm		■ Vacuum pump standard	160 or 250 m ³ / h
	depth	1050 mm			
	width	2050 mm			
■ Electrical supply standard		400V/ 3			

Technical modifications reserved!