



 **therma***line*

Modular 90

Range Overview



Thinking of you
Electrolux

thermaline: Swiss excellence

a new era in professional cooking



1871 Production, Precision
and Tradition

for over 100 years



Full flexible modular cooking line made composed of:

◆ Top units

- H=250

◆ Stand alone units

- H=700 (body height 700mm Hygienic)
- H=800 (body height 800mm)

◆ Bases

- (for installation of top units)
- H=450 (for total body height including top of 700mm hygienic)
- H=550 (for total body height of 800mm)

Units can be found in various installation Operating Side configurations:

- ◆ **Stand alone one side island operation**
(control panel found on one side)
- ◆ **Stand alone two side island operation**
(control panel found on both side of the units)
- ◆ **Stand alone one side against the wall operation** (control panel on one side with backsplash on rear of the unit)

Units can be installed on:

- ◆ **Feet** (feet can be covered with optional closing stainless steel covering plinths)
- ◆ **Stainless steel plinths**
(100mm or 200mm height)
- ◆ **On site Concrete** or stainless steel plinths
- ◆ **Wall/cantilever** configurations with optional factory supplied kit (verify with factory possible configurations certain units)

Index

Electric Solid Tops - 2 Zones	8
Electric Solid Tops - 2 Zones - Freestanding - H 700 mm	8
Electric Solid Tops - 2 Zones - Freestanding - H 800 mm	8
Electric Solid Tops - 4 Zones	8
Electric Solid Tops - 4 Zones - Freestanding - H 700 mm	9
Electric Solid Tops - 4 Zones - Freestanding - H 800 mm	9
Gas French Tops	9
Gas French Tops - Freestanding - H 700 mm	9
Gas French Tops - Freestanding - H 800 mm	10
Gas French Tops on Gas Static Oven - H 700 mm	10
Gas French Tops on Gas Static Oven - H 800 mm	10
Infrared Tops - 2 and 4 Zones	10
Induction Tops - 2 Zones	11
Induction Tops - 4 Zones	11
Induction Woks	11
Induction Woks and Plates	12
Full Surface Induction Tops on Open Base - H 700 mm	12
Full Surface Induction Tops on Open Base - H 800 mm	12
Full Surface Induction Tops on Warming Cabinet - H 700 mm	13
Full Surface Induction Tops on Warming Cabinet - H 800 mm	13
Full Surface Induction Tops on Cupboard Base - H 700 mm	13
Full Surface Induction Tops on Cupboard Base - H 800 mm	13
Full Surface Induction Tops on Electric Static Oven - H 700 mm	14
Full Surface Induction Tops on Electric Static Oven - H 800 mm	14
Gas Burner Tops - 2 Burners	14
Gas Burner Tops - 4 and 6 Burners	14
Gas Burner Tops - 2 Burners - Ecoflam	15
Gas Burner Tops - 4 and 6 Burners - Ecoflam	15
Gas Burner Tops on Gas Static Oven - H 700 mm	15
Gas Burner Tops on Gas Static Oven - H 800 mm	15
Gas Burner Tops on Gas Static Oven - Ecoflam - H 700 mm	16
Gas Burner Tops on Gas Static Oven - Ecoflam - H 800 mm	16

Electric Fry Tops - Smooth Chrome Plate	16
Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 700 mm	16
Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 800 mm	17
Electric Fry Tops - Ribbed Chrome Plate	17
Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 700 mm	17
Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 800 mm	17
Electric Fry Tops - Smooth and Ribbed Chrome Plate	18
Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 700 mm	18
Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 800 mm	18
Gas Fry Tops - Smooth Chrome Plate	18
Gas Fry Tops - Smooth Chrome Plate - Freestanding - H 700 mm	19
Gas Fry Tops - Smooth Chrome Plate - Freestanding - H 800 mm	19
Gas Fry Tops - Ribbed Chrome Plate	19
Gas Fry Tops - Ribbed Chrome Plate - Freestanding - H 700 mm	19
Gas Fry Tops - Ribbed Chrome Plate - Freestanding - H 800 mm	20
Gas Fry Tops - Smooth and Ribbed Chrome Plate	20
Gas Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 700 mm	20
Gas Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 800 mm	20
Electric Free-cooking Tops	21
Electric Free-cooking Tops - Freestanding - H 700 mm	21
Electric Free-cooking Tops - Freestanding - H 800 mm	21
Gas Chargrill Tops	21
Electric Bain Marie Tops	22
Electric Aquacookers - Freestanding - H 700 mm	22
Electric Aquacookers - Freestanding - H 800 mm	22
Electric Multi Braisers - 1/1 GN - Freestanding - H 700 mm	23
Electric Multi Braisers - 1/1 GN - Freestanding - H 800 mm	23
Electric Multi Braisers - 2/1 GN - Freestanding - H 700 mm	23
Electric Multi Braisers - 2/1 GN - Freestanding - H 800 mm	23
Pasta Cookers - Freestanding - H 700 mm	24
Pasta Cookers - Freestanding - H 800 mm	24

Electric Deep Fat Fryers - Freestanding - H 700 mm	25
Electric Deep Fat Fryers - Freestanding - H 800 mm	25
Gas Deep Fat Fryers - Freestanding - H 700 mm	26
Gas Deep Fat Fryers - Freestanding - H 800 mm	26
Electric Chip Scuttles	26
Mixing Tap Units - Freestanding - H 700 mm	26
Mixing Tap Units - Freestanding - H 800 mm	27
Mixing Tap Units - Freestanding - Automatic Water Refilling	27
Closed Work Tops - 100 to 300 mm	27
Closed Work Tops - 400 to 600 mm	27
Closed Work Tops - 700 to 900 mm	28
Closed Work Tops - 1000 to 1500 mm	28
Sink Units - Freestanding	28
Closed Bases - H 450 mm	28
Open Bases (GN Conform) - H 450 mm	29
Open Bases - H 450 mm	29
Cupboard Bases (GN Conform) - H 450 mm	29
Passthrough Open Bases (GN Conform) - H 450 mm	29
Passthrough Open Bases - H 450 mm	30
Passthrough Cupboard Bases (GN Conform) - H 450 mm	30
Closed Bases - H 550 mm	30
Open Bases (GN Conform) - H 550 mm	30
Open Bases - H 550 mm	31
Cupboard Bases (GN Conform) - H 550 mm	31
Passthrough Open Bases (GN Conform) - H 550 mm	31
Passthrough Open Bases - H 550 mm	31
Passthrough Cupboard Bases (GN Conform) - H 550 mm	32
Electric Warming Cabinet Bases (GN Conform) - H 450 mm	32
Electric Passthrough Warming Cabinet Bases (GN Conform) - H 450 mm	32
Electric Warming Cabinet Bases (GN Conform) - H 550 mm	33
Electric Passthrough Warming Cabinet Bases (GN Conform) - H 550 mm	33

Holding Cabinet Base (GN Conform) - H 450 mm	33
Holding Cabinet Base (GN Conform) - H 550 mm	34
Electric Static Oven Bases	34
Refrigerated Bases	34

Electric Solid Tops - 2 Zones



	■ 589000	■ 589001	■ 589002	■ 589003	■ 589004	■ 589005
External dim. - mm						
width	500	500	500	500	500	500
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Electric power - kW	6	6	6	6	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops - 2 Zones - Freestanding - H 700 mm



	■ 589508	■ 589509	■ 589510	■ 589511	■ 589512	■ 589513
External dim. - mm						
width	500	500	500	500	500	500
depth	900	900	900	900	900	900
height	700	700	700	700	700	700
Electric power - kW	6	6	6	6	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops - 2 Zones - Freestanding - H 800 mm



	■ 589520	■ 589521	■ 589522	■ 589523	■ 589524	■ 589525
External dim. - mm						
width	500	500	500	500	500	500
depth	900	900	900	900	900	900
height	800	800	800	800	800	800
Electric power - kW	6	6	6	6	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops - 4 Zones



	■ 589006	■ 589007	■ 589008	■ 589009	■ 589010	■ 589011
External dim. - mm						
width	1000	1000	1000	1000	1000	1000
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Electric power - kW	16	16	16	16	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops - 4 Zones - Freestanding - H 700 mm



	■ 589514	■ 589515	■ 589516	■ 589517	■ 589518	■ 589519
External dim. - mm						
width	1000	1000	1000	1000	1000	1000
depth	900	900	900	900	900	900
height	700	700	700	700	700	700
Electric power - kW	16	16	16	16	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops - 4 Zones - Freestanding - H 800 mm



	■ 589526	■ 589527	■ 589528	■ 589529	■ 589530	■ 589531
External dim. - mm						
width	1000	1000	1000	1000	1000	1000
depth	900	900	900	900	900	900
height	800	800	800	800	800	800
Electric power - kW	16	16	16	16	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Gas French Tops



	■ 589580	■ 589014
External dim. - mm		
width	1000	1000
depth	900	900
height	250	250
Gas Power - kW	12.5	12.5
Operating side	1-side	1-side
Backsplash		•

Gas French Tops - Freestanding - H 700 mm



	■ 589581	■ 589582
External dim. - mm		
width	1000	1000
depth	900	900
height	700	700
Gas Power - kW	12.5	12.5
Operating side	1-side	1-side
Backsplash		•

Gas French Tops - Freestanding - H 800 mm



	■ 589583	■ 589584
External dim. - mm		
width	1000	1000
depth	900	900
height	800	800
Gas Power - kW	12.5	12.5
Operating side	1-side	1-side
Backsplash		•

Gas French Tops on Gas Static Oven - H 700 mm



	■ 589637	■ 589638
External dim. - mm		
width	1000	1000
depth	900	900
height	700	700
Gas Power - kW	17	17
Operating side	1-side	1-side
Backsplash		•

Gas French Tops on Gas Static Oven - H 800 mm



	■ 589639	■ 589640
External dim. - mm		
width	1000	1000
depth	900	900
height	800	800
Gas Power - kW	17	17
Operating side	1-side	1-side
Backsplash		•

Infrared Tops - 2 and 4 Zones



	■ 589015	■ 589016	■ 589017	■ 589018	■ 589019	■ 589020
External dim. - mm						
width	500	500	500	1000	1000	1000
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Electric power - kW	8	8	8	16	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Zones	2	2	2	4	4	4

Induction Tops - 2 Zones



	■ 589025	■ 589026	■ 589027
External dim. - mm			
width	500	500	500
depth	900	900	900
height	250	250	250
Electric power - kW	10	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	2	2	2

Induction Tops - 4 Zones



	■ 589028	■ 589029	■ 589030
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	250	250	250
Electric power - kW	20	20	20
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	4	4	4

Induction Woks



	■ 589034	■ 589035
External dim. - mm		
width	500	500
depth	900	900
height	250	250
Electric power - kW	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
Zones	1	1
Wok	1	1

Induction Woks and Plates



	■ 589038	■ 589040	■ 589042
External dim. - mm			
width	500	500	500
depth	900	900	900
height	250	250	250
Electric power - kW	10	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	2	2	2
Wok	1, front	1, front	1, rear
Plate	1, rear	1, rear	1, front

Full Surface Induction Tops on Open Base - H 700 mm



	■ 589043	■ 589046	■ 589049	■ 589052	■ 589055	■ 589058
External dim. - mm						
width	500	500	500	1000	1000	1000
depth	900	900	900	900	900	900
height	700	700	700	700	700	700
Electric power - kW	14	14	14	28	28	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Zones	2	2	2	4	4	4
Passthrough base						•

Full Surface Induction Tops on Open Base - H 800 mm



	■ 589354	■ 589357	■ 589360	■ 589363	■ 589366	■ 589369
External dim. - mm						
width	500	500	500	1000	1000	1000
depth	900	900	900	900	900	900
height	800	800	800	800	800	800
Electric power - kW	14	14	14	28	28	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Zones	2	2	2	4	4	4
Passthrough base						•

Full Surface Induction Tops on Warming Cabinet - H 700 mm



	■ 589053	■ 589056	■ 589059
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	700	700	700
Electric power - kW	30	30	30
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	4	4	4

Full Surface Induction Tops on Warming Cabinet - H 800 mm



	■ 589364	■ 589367	■ 589370
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	800	800	800
Electric power - kW	30	30	30
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	4	4	4

Full Surface Induction Tops on Cupboard Base - H 700 mm



	■ 589054	■ 589057	■ 589060
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	700	700	700
Electric power - kW	28	28	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	4	4	4

Full Surface Induction Tops on Cupboard Base - H 800 mm



	■ 589365	■ 589368	■ 589371
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	800	800	800
Electric power - kW	28	28	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	4	4	4

Full Surface Induction Tops on Electric Static Oven - H 700 mm



	■ 589585	■ 589586	■ 589603	■ 589604	■ 589587	■ 589605
External dim. - mm						
width	1200	1200	1200	1200	1200	1200
depth	900	900	900	900	900	900
height	700	700	700	700	700	700
Electric power - kW	33	33	33	33	33	33
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	2-side	2-side
Backsplash		•		•		
Zones	4	4	4	4	4	4
Mixing tap position	left	left	right	right	left	right

Full Surface Induction Tops on Electric Static Oven - H 800 mm



	■ 589588	■ 589589	■ 589606	■ 589607	■ 589590	■ 589608
External dim. - mm						
width	1200	1200	1200	1200	1200	1200
depth	900	900	900	900	900	900
height	800	800	800	800	800	800
Electric power - kW	33	33	33	33	33	33
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	2-side	2-side
Backsplash		•		•		
Zones	4	4	4	4	4	4
Mixing tap position	left	left	right	right	left	right

Gas Burner Tops - 2 Burners



	■ 589068	■ 589069	■ 589070
External dim. - mm			
width	500	500	500
depth	900	900	900
height	250	250	250
Gas Power - kW	20	20	20
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	2	2	2

Gas Burner Tops - 4 and 6 Burners



	■ 589071	■ 589072	■ 589073	■ 589074	■ 589075	■ 589076
External dim. - mm						
width	1000	1000	1000	1500	1500	1500
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Gas Power - kW	40	40	40	60	60	60
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Burners	4	4	4	6	6	6

Gas Burner Tops - 2 Burners - Ecoflam



	■ 589079	■ 589080	■ 589081
External dim. - mm			
width	500	500	500
depth	900	900	900
height	250	250	250
Gas Power - kW	20	20	20
Operating side	1-side	1-side	2-side
Backsplash		•	
Ecoflam	•	•	•
Burners	2	2	2

Gas Burner Tops - 4 and 6 Burners - Ecoflam



	■ 589082	■ 589083	■ 589084	■ 589085	■ 589086	■ 589087
External dim. - mm						
width	1000	1000	1000	1500	1500	1500
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Gas Power - kW	40	40	40	60	60	60
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecoflam	•	•	•	•	•	•
Burners	4	4	4	6	6	6

Gas Burner Tops on Gas Static Oven - H 700 mm



	■ 589641	■ 589642	■ 589615
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	700	700	700
Gas Power - kW	47	47	47
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	4	4	4
Passthrough oven			•

Gas Burner Tops on Gas Static Oven - H 800 mm



	■ 589645	■ 589646	■ 589617
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	800	800	800
Gas Power - kW	47	47	47
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	4	4	4
Passthrough oven			•

Gas Burner Tops on Gas Static Oven - Ecoflam - H 700 mm



	■ 589643	■ 589644	■ 589616
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	700	700	700
Gas Power - kW	47	47	47
Operating side	1-side	1-side	2-side
Backsplash		•	
Ecoflam	•	•	•
Burners	4	4	4
Passthrough oven			•

Gas Burner Tops on Gas Static Oven - Ecoflam - H 800 mm



	■ 589647	■ 589648	■ 589618
External dim. - mm			
width	1000	1000	1000
depth	900	900	900
height	800	800	800
Gas Power - kW	47	47	47
Operating side	1-side	1-side	2-side
Backsplash		•	
Ecoflam	•	•	•
Burners	4	4	4
Passthrough oven			•

Electric Fry Tops - Smooth Chrome Plate



	■ 589088	■ 589089	■ 589090	■ 589091
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	250	250	250	250
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 700 mm



	■ 589532	■ 589533	■ 589534	■ 589535
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	700	700	700	700
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 800 mm



	■ 589552	■ 589553	■ 589554	■ 589555
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	800	800	800	800
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Ribbed Chrome Plate



	■ 589096	■ 589097	■ 589098	■ 589099
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	250	250	250	250
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 700 mm



	■ 589540	■ 589541	■ 589542	■ 589543
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	700	700	700	700
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 800 mm



	■ 589560	■ 589561	■ 589562	■ 589563
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	800	800	800	800
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Smooth and Ribbed Chrome Plate



	■ 589106	■ 589107
External dim. - mm		
width	800	800
depth	900	900
height	250	250
Electric power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 700 mm



	■ 589548	■ 589549
External dim. - mm		
width	800	800
depth	900	900
height	700	700
Electric power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 800 mm



	■ 589568	■ 589569
External dim. - mm		
width	800	800
depth	900	900
height	800	800
Electric power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Gas Fry Tops - Smooth Chrome Plate



	■ 589092	■ 589093	■ 589094	■ 589095
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	250	250	250	250
Gas Power - kW	10	10	20	20
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Gas Fry Tops - Smooth Chrome Plate - Freestanding - H 700 mm



	■ 589536	■ 589537	■ 589538	■ 589539
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	700	700	700	700
Gas Power - kW	10	10	20	20
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Gas Fry Tops - Smooth Chrome Plate - Freestanding - H 800 mm



	■ 589556	■ 589557	■ 589558	■ 589559
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	800	800	800	800
Gas Power - kW	10	10	20	20
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Gas Fry Tops - Ribbed Chrome Plate



	■ 589100	■ 589101	■ 589102	■ 589103
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	250	250	250	250
Gas Power - kW	10	10	20	20
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Gas Fry Tops - Ribbed Chrome Plate - Freestanding - H 700 mm



	■ 589544	■ 589545	■ 589546	■ 589547
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	700	700	700	700
Gas Power - kW	10	10	20	20
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Gas Fry Tops - Ribbed Chrome Plate - Freestanding - H 800 mm



	■ 589564 ■	■ 589565 ■	■ 589566 ■	■ 589567 ■
External dim. - mm				
width	400	400	800	800
depth	900	900	900	900
height	800	800	800	800
Gas Power - kW	10	10	20	20
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Gas Fry Tops - Smooth and Ribbed Chrome Plate



	■ 589110 ■	■ 589111 ■
External dim. - mm		
width	800	800
depth	900	900
height	250	250
Gas Power - kW	20	20
Operating side	1-side	1-side
Backsplash		•

Gas Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 700 mm



	■ 589550 ■	■ 589551 ■
External dim. - mm		
width	800	800
depth	900	900
height	700	700
Gas Power - kW	20	20
Operating side	1-side	1-side
Backsplash		•

Gas Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 800 mm



	■ 589570 ■	■ 589571 ■
External dim. - mm		
width	800	800
depth	900	900
height	800	800
Gas Power - kW	20	20
Operating side	1-side	1-side
Backsplash		•

Electric Free-cooking Tops



	■ 589126	■ 589127	■ 589130	■ 589131
External dim. - mm				
width	500	500	1000	1000
depth	900	900	900	900
height	250	250	250	250
Electric power - kW	6	6	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Free-cooking Tops - Freestanding - H 700 mm



	■ 589572	■ 589573	■ 589574	■ 589575
External dim. - mm				
width	500	500	1000	1000
depth	900	900	900	900
height	700	700	700	700
Electric power - kW	6	6	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Free-cooking Tops - Freestanding - H 800 mm



	■ 589576	■ 589577	■ 589578	■ 589579
External dim. - mm				
width	500	500	1000	1000
depth	900	900	900	900
height	800	800	800	800
Electric power - kW	6	6	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Gas Chargrill Tops



	■ 589278	■ 589279	■ 589280	■ 589281	■ 589282	■ 589283
External dim. - mm						
width	400	400	800	800	1200	1200
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Gas Power - kW	10.5	10.5	21	21	31.5	31.5
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

Electric Bain Marie Tops



	■ 589132	■ 589133	■ 589633	■ 589634	■ 589635	■ 589636
External dim. - mm						
width	400	400	500	500	500	500
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Electric power - kW	1.5	1.5	1.5	1.5	1.5	1.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
GN size	1/1	1/1	1/1	1/1	1/1	1/1
Mixing tap position	rear	rear	left	left	right	right

Electric Bain Marie Tops



	■ 589134	■ 589135
External dim. - mm		
width	800	800
depth	900	900
height	250	250
Electric power - kW	3	3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
GN size	2/1	2/1
Mixing tap position	rear	rear

Electric Aquacookers - Freestanding - H 700 mm



	■ 589138	■ 589139
External dim. - mm		
width	400	400
depth	900	900
height	700	700
Electric power - kW	7.5	7.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
El. control	•	•

Electric Aquacookers - Freestanding - H 800 mm



	■ 589377	■ 589378
External dim. - mm		
width	400	400
depth	900	900
height	800	800
Electric power - kW	7.5	7.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
El. control	•	•

Electric Multi Braisers - 1/1 GN - Freestanding - H 700 mm



	■ 589266	■ 589267
External dim. - mm		
width	400	400
depth	900	900
height	700	700
Electric power - kW	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Multi Braisers - 1/1 GN - Freestanding - H 800 mm



	■ 589435	■ 589436
External dim. - mm		
width	400	400
depth	900	900
height	800	800
Electric power - kW	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Multi Braisers - 2/1 GN - Freestanding - H 700 mm



	■ 589272	■ 589273
External dim. - mm		
width	800	800
depth	900	900
height	700	700
Electric power - kW	10.2	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Multi Braisers - 2/1 GN - Freestanding - H 800 mm



	■ 589441	■ 589442
External dim. - mm		
width	800	800
depth	900	900
height	800	800
Electric power - kW	10.2	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Pasta Cookers - Freestanding - H 700 mm



	■ 589290	■ 589291	■ 589471	■ 589472	■ 589473	■ 589474
External dim. - mm						
width	400	400	400	400	400	400
depth	900	900	900	900	900	900
height	700	700	700	700	700	700
Gas Power - kW					10.5	10.5
Electric power - kW	5	5	6	6		
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz		
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Tank capacity - lt	5x2	5x2	20	20	20	20

Pasta Cookers - Freestanding - H 700 mm



	■ 589292	■ 589293
External dim. - mm		
width	400	400
depth	900	900
height	700	700
Electric power - kW	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
Tank capacity - lt	40	40

Pasta Cookers - Freestanding - H 800 mm



	■ 589447	■ 589448	■ 589475	■ 589476	■ 589477	■ 589478
External dim. - mm						
width	400	400	400	400	400	400
depth	900	900	900	900	900	900
height	800	800	800	800	800	800
Gas Power - kW					10.5	10.5
Electric power - kW	5	5	6	6		
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz		
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Tank capacity - lt	5x2	5x2	20	20	20	20

Pasta Cookers - Freestanding - H 800 mm



	■ 589449	■ 589450
External dim. - mm		
width	400	400
depth	900	900
height	800	800
Electric power - kW	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
Tank capacity - lt	40	40

Electric Deep Fat Fryers - Freestanding - H 700 mm



	■ 589296	■ 589297	■ 589298	■ 589299
External dim. - mm				
width	400	400	400	400
depth	900	900	900	900
height	700	700	700	700
Electric power - kW	5.4	5.4	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	7	7	5X2	5X2

Electric Deep Fat Fryers - Freestanding - H 700 mm



	■ 589498	■ 589499	■ 589300	■ 589301
External dim. - mm				
width	400	400	500	500
depth	900	900	900	900
height	700	700	700	700
Electric power - kW	10	10	18	18
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	14	14	23	23

Electric Deep Fat Fryers - Freestanding - H 800 mm



	■ 589453	■ 589454	■ 589455	■ 589456
External dim. - mm				
width	400	400	400	400
depth	900	900	900	900
height	800	800	800	800
Electric power - kW	5.4	5.4	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	7	7	5X2	5X2

Electric Deep Fat Fryers - Freestanding - H 800 mm



	■ 589500	■ 589501	■ 589457	■ 589458
External dim. - mm				
width	400	400	500	500
depth	900	900	900	900
height	800	800	800	800
Electric power - kW	10	10	18	18
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	14	14	23	23

Gas Deep Fat Fryers - Freestanding - H 700 mm



	■ 589504	■ 589505	■ 589302	■ 589303
External dim. - mm				
width	400	400	500	500
depth	900	900	900	900
height	700	700	700	700
Gas Power - kW	14	14	21	21
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	14	14	23	23

Gas Deep Fat Fryers - Freestanding - H 800 mm



	■ 589506	■ 589507	■ 589459	■ 589460
External dim. - mm				
width	400	400	500	500
depth	900	900	900	900
height	800	800	800	800
Gas Power - kW	14	14	21	21
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	14	14	23	23

Electric Chip Scuttles



	■ 589142	■ 589143
External dim. - mm		
width	400	400
depth	900	900
height	250	250
Electric power - kW	1	1
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
GN Size	1/1	1/1

Mixing Tap Units - Freestanding - H 700 mm



	■ 589591	■ 589592	■ 589593	■ 589594
External dim. - mm				
width	200	200	200	200
depth	900	900	900	900
height	700	700	700	700
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Lever	•	•		
Knobs			•	•

Mixing Tap Units - Freestanding - H 800 mm



	■ 589595	■ 589596	■ 589597	■ 589598
External dim. - mm				
width	200	200	200	200
depth	900	900	900	900
height	800	800	800	800
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Lever	•	•		
Knobs			•	•

Mixing Tap Units - Freestanding - Automatic Water Refilling



	■ 589221	■ 589222	■ 589390	■ 589391
External dim. - mm				
width	200	200	200	200
depth	900	900	900	900
height	700	700	800	800
Electric power - kW	0.1	0.1	0.1	0.1
Electrical connection	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Closed Work Tops - 100 to 300 mm



	■ 589150	■ 589151	■ 589152	■ 589153	■ 589154	■ 589155
External dim. - mm						
width	100	100	200	200	300	300
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

Closed Work Tops - 400 to 600 mm



	■ 589156	■ 589157	■ 589158	■ 589159	■ 589160	■ 589161
External dim. - mm						
width	400	400	500	500	600	600
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

Closed Work Tops - 700 to 900 mm



	■ 589162	■ 589163	■ 589164	■ 589165	■ 589166	■ 589167
External dim. - mm						
width	700	700	800	800	900	900
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

Closed Work Tops - 1000 to 1500 mm



	■ 589168	■ 589169	■ 589170	■ 589171	■ 589172	■ 589173
External dim. - mm						
width	1000	1000	1200	1200	1500	1500
depth	900	900	900	900	900	900
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

Sink Units - Freestanding



	■ 589308	■ 589309	■ 589465	■ 589466
External dim. - mm				
width	400	400	400	400
depth	900	900	900	900
height	700	700	800	800
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Closed Bases - H 450 mm



	■ 589599	■ 589601	■ 589631
External dim. - mm			
width	100	200	300
depth	900	900	900
height	450	450	450

Open Bases (GN Conform) - H 450 mm



	■ 589174	■ 589179	■ 589180	■ 589496	■ 589181
External dim. - mm					
width	400	500	600	700	800
depth	900	900	900	900	900
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN

Open Bases - H 450 mm



	■ 589175	■ 589176	■ 589177	■ 589178
External dim. - mm				
width	900	1000	1200	1500
depth	900	900	900	900
height	450	450	450	450
Operating side	1-side	1-side	1-side	1-side

Cupboard Bases (GN Conform) - H 450 mm



	■ 589182	■ 589183	■ 589184	■ 589186	■ 589185
External dim. - mm					
width	400	500	600	800	1000
depth	900	900	900	900	900
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN
Doors	1	1	1	2	2

Passthrough Open Bases (GN Conform) - H 450 mm



	■ 589193	■ 589194	■ 589188	■ 589195
External dim. - mm				
width	500	600	700	800
depth	900	900	900	900
height	450	450	450	450
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Passthrough base	•	•	•	•

Passthrough Open Bases - H 450 mm



	■ 589189	■ 589190	■ 589191	■ 589192
External dim. - mm				
width	900	1000	1200	1500
depth	900	900	900	900
height	450	450	450	450
Operating side	2-side	2-side	2-side	2-side
Passthrough base	•	•	•	•

Passthrough Cupboard Bases (GN Conform) - H 450 mm



	■ 589196	■ 589197	■ 589201	■ 589199	■ 589200
External dim. - mm					
width	500	600	800	1000	1200
depth	900	900	900	900	900
height	450	450	450	450	450
Operating side	2-side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN	GN
Doors	2	2	4	4	4
Passthrough base	•	•	•		

Closed Bases - H 550 mm



	■ 589600	■ 589602	■ 589632
External dim. - mm			
width	100	200	300
depth	900	900	900
height	550	550	550

Open Bases (GN Conform) - H 550 mm



	■ 589310	■ 589315	■ 589316	■ 589497	■ 589317
External dim. - mm					
width	400	500	600	700	800
depth	900	900	900	900	900
height	550	550	550	550	550
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN

Open Bases - H 550 mm



	■ 589311	■ 589312	■ 589313	■ 589314
External dim. - mm				
width	900	1000	1200	1500
depth	900	900	900	900
height	550	550	550	550
Operating side	1-side	1-side	1-side	1-side

Cupboard Bases (GN Conform) - H 550 mm



	■ 589318	■ 589319	■ 589320	■ 589322	■ 589321
External dim. - mm					
width	400	500	600	800	1000
depth	900	900	900	900	900
height	550	550	550	550	550
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN
Doors	1	1	1	2	2

Passthrough Open Bases (GN Conform) - H 550 mm



	■ 589329	■ 589330	■ 589324	■ 589331
External dim. - mm				
width	500	600	700	800
depth	900	900	900	900
height	550	550	550	550
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Passthrough base	•	•	•	•

Passthrough Open Bases - H 550 mm



	■ 589325	■ 589326	■ 589327	■ 589328
External dim. - mm				
width	900	1000	1200	1500
depth	900	900	900	900
height	550	550	550	550
Operating side	2-side	2-side	2-side	2-side
Passthrough base	•	•	•	•

Passthrough Cupboard Bases (GN Conform) - H 550 mm



	■ 589332	■ 589333	■ 589337	■ 589335	■ 589336
External dim. - mm					
width	500	600	800	1000	1200
depth	900	900	900	900	900
height	550	550	550	550	550
Operating side	2-side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN	GN
Doors	2	2	4	4	4
Passthrough base	•	•	•	•	•

Electric Warming Cabinet Bases (GN Conform) - H 450 mm



	■ 589479	■ 589480	■ 589481	■ 589482
External dim. - mm				
width	500	600	800	1000
depth	900	900	900	900
height	450	450	450	450
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN
Doors	1	1	2	2

Electric Passthrough Warming Cabinet Bases (GN Conform) - H 450 mm



	■ 589483	■ 589484	■ 589485	■ 589486
External dim. - mm				
width	500	600	800	1000
depth	900	900	900	900
height	450	450	450	450
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Doors	2	2	4	4
Passthrough base	•	•	•	•

Electric Warming Cabinet Bases (GN Conform) - H 550 mm



	■ 589487	■ 589488	■ 589489	■ 589490
External dim. - mm				
width	500	600	800	1000
depth	900	900	900	900
height	550	550	550	550
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN
Doors	1	1	2	2

Electric Passthrough Warming Cabinet Bases (GN Conform) - H 550 mm



	■ 589491	■ 589492	■ 589493	■ 589494
External dim. - mm				
width	500	600	800	1000
depth	900	900	900	900
height	550	550	550	550
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Doors	2	2	4	4
Passthrough base	•	•	•	•

Holding Cabinet Base (GN Conform) - H 450 mm



	■ 589467
External dim. - mm	
width	800
depth	900
height	450
Electric power - kW	1
Electrical connection	230V 1N 50Hz
Operating side	1-side
Drawers (2)	•

Holding Cabinet Base (GN Conform) - H 550 mm




	■ 589469
External dim. - mm	
width	800
depth	900
height	550
Electric power - kW	1
Electrical connection	230V 1N 50Hz
Operating side	1-side
Drawers (2)	•

Electric Static Oven Bases



	■ 589609	■ 589610	■ 589611	■ 589612
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	450	450	550	550
Electric power - kW	5	5	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Passthrough base		•		•

Refrigerated Bases



	■ 589344	■ 589345
External dim. - mm		
width	1000	1200
depth	900	900
height	550	550
Electric power - kW	0.67	0.5
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz
Operating side	1-side	1-side

Excellence with the environment in mind

Electrolux Professional solutions perfectly match the customers' needs, including the areas of reliability, cost efficiency and sustainability. The products are the best in terms of quality - durability with low running costs. Some installations have been running for more than 40 years!

- All Electrolux Professional factories are ISO 14001-certified
- All Electrolux Professional solutions are designed for low water, energy and detergent consumption, and for low emissions into the environment
- All Electrolux Professional solutions are the best-in-class in terms of quality, for a long life cycle with the lowest life cycle costs. There are solutions still running after 40 years
- All Electrolux Professional solutions are ROHS and REACH-compliant and over 95% recyclable
- All Electrolux Professional solutions are 100% quality tested and all of the functions are singularly checked by expert technicians
- In the last five years, more than 70% of Electrolux Professional solutions have been updated with features that are always designed with the needs of customers and environmental considerations in mind
- Electrolux Professional sustains a specific energy saving program to reduce the energy consumption of its production plants



Thinking of you
Electrolux