

## Tabel-Top-Model EST 15 Series

## Vacuum-Packing-Machines

### LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealingbar, counterbar, hinges
- Soft Air reventilation of the chamber
- Acrylicglas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

### Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Tabel-Top-Model: EST 15 LS



Tabel-Top-Model:

Technical Data		EST 15
■ Chamber size inside	height	115 mm
	depth	405 mm
	width	305 mm
■ External dimensions	height	345 mm
	depth	586 mm
	width	365 mm
■ Weight		49 kg
■ Length of sealing-bar		300 mm
■ Packaging performance		2 min.
■ Vacuum pump standard		16 m <sup>3</sup> / h
■ Electrical supply standard	LC: 230V / 1 or on request LS: 400V / 3 or on request	

*Technische Änderungen vorbehalten  
Technical modifications reserved*