

Tabel-Top-Model EST 30 F / 32 F

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



EST 30 LS



Control panel LC

Technical Data		EST 30 F / EST 32 F	Technical Data		EST 30 F / EST 32 F	
■ Chamber size inside	height	110 mm	■ Weight	85 kg or 105 kg		
	depth	356 mm		■ Length of sealing bar	350 mm or 890 mm	
	width	900 mm				
■ External dimensions	height	390 mm	■ Packaging performance	1 to 2/min. or 1 bis 3/min.		
	depth	560 mm		■ Vacuum pump standard	21 m ³ / h or 42 m ³ / h	
	width	970 mm				
■ Electrical supply standard		LC: 230V / 1 or on request	LS: 400V / 3 or on request			

Technical modifications reserved