

Williams
Professional Refrigeration

Beverage Counter Series

Drinks display and storage are essential to catering,
Williams provides ranges of equipment
to facilitate your business



Bottle Cooler Key Features

Designed for stylish, effective storage and display of bottles and cans for easy customer selection



- 01. Fitted with anti-condensation double glazed Argon gas glass door with aluminium alloy frame
- 02. Bright low energy LED with on / off switch for excellent product display and easy customer selection
- 03. Engineered with hidden condensing unit to fit with interior design and minimising the requested installation space
- 04. Fully adjustable perforated 304 grade stainless steel shelves. Accommodates a vertical stacking capacity of three or six levels of 10" bottles
- 05. Excellent thermal efficiency, high density polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
- 06. Removable magnetic door gasket with air release points provides an excellent seal to prevent heat ingress
- 07. BC1, BC2 and BC3: 10Hmm levelling feet at front to ensure stability on an uneven floor and 15Hmm castors at rear
- 08. BC95 and BC200: 10Hmm levelling feet to ensure stability on an uneven floor
- 09. Forced air refrigeration system ensures effective air circulation
- 10. Imported, durable and energy-efficient compressor
- 11. Evaporator with Hydrophilic coated aluminum provides high corrosion resistance properties
- 12. Accurate helium leak detection system ensures the quality of the entire refrigeration system
- 13. Automatic defrost ensures the evaporator working to its optimum performance
- 14. Automatically vaporises defrost water, drainage is not required
- 15. Designed and engineered to operate up to 32°C ambient
- 16. Environmental-friendly CFC-free refrigerant (R134a)
- 17. HACCP compliant

Bottle Cooler

Specification

- Foodsafe 304 grade stainless steel exterior and 304 grade BA mirror stainless steel interior
- Galvanised steel exterior back and base
- Fitted with cylindrical lock

Options

1. 304 grade stainless steel exterior back / base
2. Black colour bond exterior / back
3. 15mm thick table top for hidden the door hinge screw *
4. 304 grade stainless steel door
5. Left-hand-side door hinge
6. Additional shelving / shelf supporters
7. 220V / 60HZ / 1PH

* Available for BC1SS, BC2SS and BC3SS only



Bottle Cooler Product List



Bottle Cooler Technical Data

Model	BC1SS / BC1SS-U	BC2SS / BC2SS-U	BC3SS / BC3SS-U	BC95SS	BC200SS
Temp Range (°C)	+4 / +10	+4 / +10	+4 / +10	+4 / +10	+4 / +10
External Dimension (mm)					
Width	600	900	1352	645	1290
Depth (including 27mm rear bracket)	530			635	
Height	895 800 (-U)			1770	
Internal Dimension (mm)					
Width	530	830	1310	545	1190
Depth	378			460	
Height	745 650 (-U)			1554	
Thickness of 304 grade stainless steel (mm)					
Exterior	0.7				
Interior	0.7				
Opening Depth (mm)	1073	923		1254	
Capacity (cu.ft / litres)	5.3 / 152 4.5 / 130 (-U)	8.4 / 238 7.2 / 204 (-U)	13 / 368 11.1 / 315 (-U)	14.5 / 412	31.7 / 899
Capacity (cans @ 330ml)	122	204	309	266	558
Power Supply	220V / 50HZ / 1PH 13 amp plug				
Power Input - Running (amps)	2	3.5	2	2.28	
Rating Power (watts) *	440	770	440	502	
Compressor (HP)	1/5	1/4	1/5	1/4	
Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)	287	485	287	485	
Refrigerant	R134a				
Standard fittings					
Stainless steel perforated shelves	2		6		12
Shelf supporters	8	10	24	48	

* 20% increase for 60HZ power supply

V4

Wall Mounted Bottle Cooler

Specification

- Foodsafe 304 grade stainless steel exterior (including base) and 304 grade BA mirror stainless steel interior
- Galvanised steel exterior back
- Fitted with cylindrical lock
- With wall mount bracket

Product List



Wall Mounted Bottle Cooler

Technical Data

Model	BCWM-1	BCWM-2	BCWM-3
Temp Range (°C)	+4 / +10	+4 / +10	+4 / +10
External Dimension (mm)			
Width	600	900	1352
Depth	450		
Height	835		
Internal Dimension (mm)			
Width	530	830	1275
Depth	310		
Height	490		
Thickness of 304 grade stainless steel (mm)			
Exterior	0.7		
Interior	0.7		
Opening Depth (mm)	1005	860	
Capacity (cu.ft / litres)	3.5 / 100	5.5 / 155	8.2 / 230
Capacity (cans @ 330ml)	96	120	180
Power Supply	220V / 50HZ / 1PH 13 amp plug		
Power Input - Running (amps)	2	3.5	
Rating Power (watts) *	440	770	
Compressor (HP)	1/5	1/4	
Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)	287	485	
Refrigerant	R134a		
Standard fittings			
Stainless steel perforated shelves	2	6	
Shelf supporters	8	12	24

* 20% increase for 60HZ power supply

v4