

Standmodel Expo 200 Series

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

Additional Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Expo 200 LS



Control panel LC

Technical Data		Expo 200
■ Chamber size inside	height	250 mm
	depth	606 mm
	width	806 mm
■ External dimensions	height	970 mm
	depth	805 mm
	width	875 mm
■ Weight		180 kg
■ Length of sealing bar		600 mm 800 mm
■ Packaging performance		1 to 3 / min.
■ Vacuum pump standard		100 m ³ / h
■ Electrical supply standard		LS: 400V/ 3 or on request

Technical modifications reserved!