



 **therma***line*

Modular 85

**Range Overview**



*Thinking of you*  
**Electrolux**

# thermaline: Swiss excellence

a new era in professional cooking



**1871** Production, Precision  
and Tradition

for over 100 years



**Full flexible modular cooking line made composed of:**

◆ **Top units**

H=250

◆ **Stand alone units**

H=700 (body height 700mm Hygienic)

◆ **Bases**

(for installation of top units)

H=450 (for total body height including top of 700mm hygienic)

**Units can be found in various installation  
Operating Side configuration:**

- ◆ **Stand alone one side against the wall operation** (control panel on one side with backsplash on rear of the unit)

**Units can be installed on:**

- ◆ **Feet** (feet can be covered with optional closing stainless steel covering plinths)
- ◆ **Stainless steel plinths** (100mm or 200mm height)
- ◆ **On site Concrete** or stainless steel plinths
- ◆ **Wall/cantilever** configurations with optional factory supplied kit (verify with factory possible configurations)

## Index

Electric Solid Tops	6
Electric Solid Tops - Freestanding	6
Gas French Tops	6
Infrared Tops	7
Induction Tops	7
Induction Wok and Wok and Plates	7
Full Surface Induction Tops on Bases	8
Full Surface Induction Tops on Bases - H2	8
Full Surface Induction Tops on Electric Static Oven	8
Gas Burner Tops	9
Gas Burner Tops - Ecoflam	9
Gas Burner Tops on Gas Static Oven	9
Electric Fry Tops - Chrome Plate	10
Electric Fry Tops - Chrome Plate - Freestanding	10
Gas Fry Tops - Chrome Plate	10
Gas Fry Tops - Chrome Plate - Freestanding	11
Electric Free-cooking Tops	11
Gas Chargrill Tops	11
Electric Bain Marie Tops	11
Electric Aquacooker - Freestanding	12
Electric Multi Braisers - Freestanding	12
Pasta Cookers - Freestanding	12
Deep Fat Fryers - Freestanding	12
Electric Chip Scuttle	13

Mixing Tap Units - Freestanding	13
Closed Work Tops - 100 to 600 mm	13
Closed Work Tops - 700 to 1500 mm	13
Sink Unit - Freestanding	14
Closed Bases	14
Open Bases (GN Conform)	14
Open Bases	14
Cupboard Bases	15
Open Bases (GN Conform) - H2	15
Open Bases - H2	15
Cupboard Bases - H2	15
Electric Warming Cabinet Bases	16
Electric Warming Cabinet Bases - H2	16
Holding Cabinet Base	16
Electric Static Oven Base	16

## Electric Solid Tops



	588500	588501	588502	588503
External dim. - mm				
width	500	500	800	800
depth	850	850	850	850
height	250	250	250	250
Electric power - kW	6	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•
Zones	2	2	4	4
Ecotop		•		•

## Electric Solid Tops - Freestanding



	588680	588681	588682	588683
External dim. - mm				
width	500	500	800	800
depth	850	850	850	850
height	700	700	700	700
Electric power - kW	6	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•
Zones	2	2	4	4
Open base	•	•	•	•
Ecotop		•		•

## Gas French Tops



	588504	588690	588684
External dim. - mm			
width	800	800	800
depth	850	850	850
height	250	700	700
Gas Power - kW	10	17	10
Operating side	1-side	1-side	1-side
Backsplash	•	•	•
Open base			•
Gas static oven		•	

## Infrared Tops



	588505	588506
External dim. - mm		
width	400	800
depth	850	850
height	250	250
Electric power - kW	8	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash	•	•
Zones	2	4

## Induction Tops



	588508	588509
External dim. - mm		
width	400	800
depth	850	850
height	250	250
Electric power - kW	10	20
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash	•	•
Zones	2	4

## Induction Wok and Wok and Plates



	588511	588512
External dim. - mm		
width	400	400
depth	850	850
height	250	250
Electric power - kW	5	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash	•	•
Zones	1	2
Wok	1	1 - front
Plate		1 - rear

## Full Surface Induction Tops on Bases



	588660	588661	588662
External dim. - mm			
width	1000	1000	1000
depth	850	850	850
height	700	700	700
Electric power - kW	28	30	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side
Backsplash	•	•	•
Zones	4	4	4
Open base	•		
Warming cabinet		•	
Base with doors			•

## Full Surface Induction Tops on Bases - H2



	588514	588517	588518	588519
External dim. - mm				
width	500	1000	1000	1000
depth	850	850	850	850
height	700	700	700	700
Electric power - kW	14	28	30	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•
Zones	2	4	4	4
Open base	H2	H2		
Warming cabinet			H2	
Base with doors				H2

## Full Surface Induction Tops on Electric Static Oven



	588663	588664
External dim. - mm		
width	1200	1200
depth	850	850
height	700	700
Electric power - kW	33	33
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash	•	•
Zones	4	4
Static oven	•	•
Mixing tap position	left	right



### Gas Burner Tops



	588523	588524	588525
External dim. - mm			
width	400	800	1200
depth	850	850	850
height	250	250	250
Gas Power - kW	14	28	42
Operating side	1-side	1-side	1-side
Backsplash	•	•	•
Burners	2	4	6

also available with 10 kW burners

### Gas Burner Tops - Ecoflam



	588527	588528	588529
External dim. - mm			
width	400	800	1200
depth	850	850	850
height	250	250	250
Gas Power - kW	14	28	42
Operating side	1-side	1-side	1-side
Backsplash	•	•	•
Ecoflam	•	•	•
Burners	2	4	6

also available with 10 kW burners

### Gas Burner Tops on Gas Static Oven



	588691	588692
External dim. - mm		
width	800	800
depth	850	850
height	700	700
Gas Power - kW	35	35
Operating side	1-side	1-side
Backsplash	•	•
Ecoflam		•
Burners	4	4
Gas static oven	•	•

also available with 10 kW burners

### Electric Fry Tops - Chrome Plate



	588530	588534	588531	588535	588539
External dim. - mm					
width	400	400	800	800	800
depth	850	850	850	850	850
height	250	250	250	250	250
Electric power - kW	5.1	5.1	15.3	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•	•
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•

### Electric Fry Tops - Chrome Plate - Freestanding



	588665	588669	588666	588670	588674
External dim. - mm					
width	400	400	800	800	800
depth	850	850	850	850	850
height	700	700	700	700	700
Electric power - kW	5.1	5.1	15.3	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•	•
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•

### Gas Fry Tops - Chrome Plate



	588532	588536	588533	588537	588541
External dim. - mm					
width	400	400	800	800	800
depth	850	850	850	850	850
height	250	250	250	250	250
Gas Power - kW	10	10	20	20	20
Operating side	1-side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•	•
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•

### Gas Fry Tops - Chrome Plate - Freestanding



	588667	588671	588668	588672	588676
External dim. - mm					
width	400	400	800	800	800
depth	850	850	850	850	850
height	700	700	700	700	700
Gas Power - kW	10	10	20	20	20
Operating side	1-side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•	•
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•

### Electric Free-cooking Tops



	588549	588551	588677	588678
External dim. - mm				
width	500	800	500	800
depth	850	850	850	850
height	250	250	700	700
Electric power - kW	6	12	6	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•

### Gas Chargrill Tops



	588618	588619	588620
External dim. - mm			
width	400	800	1200
depth	850	850	850
height	250	250	250
Gas Power - kW	10.5	21	31.5
Operating side	1-side	1-side	1-side
Backsplash	•	•	•

### Electric Bain Marie Tops



	588552	588553
External dim. - mm		
width	400	800
depth	850	850
height	250	250
Electric power - kW	1.5	3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side

### Electric Aquacooker - Freestanding



	588554
External dim. - mm	
width	400
depth	850
height	700
Electric power - kW	7.5
Electrical connection	400V 3N 50/60Hz
Operating side	1-side
El. control	•

### Electric Multi Braisers - Freestanding



	588612	588615
External dim. - mm		
width	400	800
depth	850	850
height	700	700
Electric power - kW	5	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash	•	•
GN size	1/1	2/1

### Pasta Cookers - Freestanding



	588624	588625	588626	588627
External dim. - mm				
width	400	400	400	400
depth	850	850	850	850
height	700	700	700	700
Gas Power - kW			10.5	
Electric power - kW	5	6		10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz		400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•
Tank capacity - lt	5x2	20	20	40

### Deep Fat Fryers - Freestanding



	588629	588630	588685	588687	588631	588632
External dim. - mm						
width	400	400	400	400	500	500
depth	850	850	850	850	850	850
height	700	700	700	700	700	700
Gas Power - kW				14		21
Electric power - kW	5.4	12	10		18	
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz		400V 3N 50/60Hz	
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•	•	•
Tank capacity - lt	7	5x2	14	14	23	23

### Electric Chip Scuttle



	588556
External dim. - mm	
width	400
depth	850
height	250
Electric power - kW	1
Electrical connection	230V 1N 50/60Hz
Operating side	1-side
Backsplash	•

### Mixing Tap Units - Freestanding



	588558	588559	588597
External dim. - mm			
width	200	200	200
depth	850	850	850
height	700	700	700
Electric power - kW			0.1
Electrical connection			230V 1N 50/60Hz
Operating side	1-side	1-side	1-side
Backsplash	•	•	•
Lever	•		
Knobs		•	
Automatic			•
Electronic control			•

### Closed Work Tops - 100 to 600 mm



	588560	588561	588562	588563	588564	588565
External dim. - mm						
width	100	200	300	400	500	600
depth	850	850	850	850	850	850
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•	•	•

### Closed Work Tops - 700 to 1500 mm



	588566	588567	588568	588569	588570	588571
External dim. - mm						
width	700	800	900	1000	1200	1500
depth	850	850	850	850	850	850
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash	•	•	•	•	•	•

## Sink Unit - Freestanding



	588635
External dim. - mm	
width	400
depth	850
height	700
Operating side	1-side
Backsplash	•

## Closed Bases



	588688	588689	588693
External dim. - mm			
width	100	200	300
depth	850	850	850
height	450	450	450

## Open Bases (GN Conform)



	588636	588641	588642	588679	588643
External dim. - mm					
width	400	500	600	700	800
depth	850	850	850	850	850
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN

## Open Bases



	588637	588638	588639	588640
External dim. - mm				
width	900	1000	1200	1500
depth	850	850	850	850
height	450	450	450	450
Operating side	1-side	1-side	1-side	1-side

### Cupboard Bases



	588644	588645	588646	588648	588647
External dim. - mm					
width	400	500	600	800	1000
depth	850	850	850	850	850
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN
Doors	1	1	1	2	2

### Open Bases (GN Conform) - H2



	588572	588577	588578	588659	588579
External dim. - mm					
width	400	500	600	700	800
depth	850	850	850	850	850
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN
Hygiene class	H2	H2	H2	H2	H2

### Open Bases - H2



	588573	588574	588575	588576
External dim. - mm				
width	900	1000	1200	1500
depth	850	850	850	850
height	450	450	450	450
Operating side	1-side	1-side	1-side	1-side
Hygiene class	H2	H2	H2	H2

### Cupboard Bases - H2



	588580	588581	588582	588584	588583
External dim. - mm					
width	400	500	600	800	1000
depth	850	850	850	850	850
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN
Doors	1	1	1	2	2
Hygiene class	H2	H2	H2	H2	H2

## Electric Warming Cabinet Bases



	588655	588656	588657	588658
External dim. - mm				
width	500	600	800	1000
depth	850	850	850	850
height	450	450	450	450
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN
Doors	1	1	2	2

## Electric Warming Cabinet Bases - H2



	588651	588652	588653	588654
External dim. - mm				
width	500	600	800	1000
depth	850	850	850	850
height	450	450	450	450
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN
Doors	1	1	2	2
Hygiene class	H2	H2	H2	H2

## Holding Cabinet Base



	588649
External dim. - mm	
width	800
depth	850
height	450
Electric power - kW	1
Electrical connection	230V 1N 50Hz
Operating side	1-side
Capacity	1/1 GN
Drawers (2)	•

## Electric Static Oven Base



	588587
External dim. - mm	
width	800
depth	850
height	450
Electric power - kW	5
Electrical connection	400V 3N 50/60Hz
Operating side	1-side
Static	•









## Excellence with the environment in mind

Electrolux Professional solutions perfectly match the customers' needs, including the areas of reliability, cost efficiency and sustainability. The products are the best in terms of quality - durability with low running costs. Some installations have been running for more than 40 years!

- All Electrolux Professional factories are ISO 14001-certified
- All Electrolux Professional solutions are designed for low water, energy and detergent consumption, and for low emissions into the environment
- All Electrolux Professional solutions are the best-in-class in terms of quality, for a long life cycle with the lowest life cycle costs. There are solutions still running after 40 years
- All Electrolux Professional solutions are ROHS and REACH-compliant and over 95% recyclable
- All Electrolux Professional solutions are 100% quality tested and all of the functions are singularly checked by expert technicians
- In the last five years, more than 70% of Electrolux Professional solutions have been updated with features that are always designed with the needs of customers and environmental considerations in mind
- Electrolux Professional sustains a specific energy saving program to reduce the energy consumption of its production plants



*Thinking of you*  
**Electrolux**