

Double Chamber Machines DK 400 and DK 600

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Vacuum-chamber and casing complete stainless steel!
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealingbar, counterbar, hinges
- Soft Air reventilation of the chamber
- Acrylicglas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



DK 600 LS



Control panel LC

Technical Data		DK 400 / DK 600	Technical Data		DK 400 / DK 600	
■ Chamber size	height	210 mm / 210 mm	■ Weight	210 kg / 240 kg		
	depth	470 (570*) / 610 mm		■ Length of sealing-bar	2 x 460 mm / 4 x 600 mm	
	width	470 mm / 605 mm			■ Packaging performance	1-2 / min.
■ External dimensions	height	970 mm / 970 mm	■ Vacuum pump standard	40 m ³ / h / 63 m ³ / h		
	depth	660 mm / 805 mm				
	width	1.110 mm / 1.390 mm				
■ Electrical supply standard		400V/ 3				

Technical modifications reserved!