

















EM Series Restaurant
Range Line
Compact Line

Electrolux



Thinking of you
Electrolux

Index

	Gas Boiling Tops without Safety Thermocouple	4
	Gas Boiling Tops without Safety Thermocouple	4
	Gas Ranges	4
	Gas Ranges	5
	Induction Cooking Tops	5
	Gas French (Solid) Tops	5
	Smooth Gas Griddles without Piezo Ignition	6
	Ribbed Gas Griddles without Piezo Ignition	6
	Smooth Gas Griddles without Piezo Ignition	6
	Ribbed Gas Griddles without Piezo Ignition	7
	Smooth Gas Griddles with Piezo Ignition	7
	Ribbed Gas Griddles with Piezo Ignition	7
	Gas Charbroilers	8
	Gas Charbroilers	8
	Gas Fryers	8
	Gas Pastacookers	9
	Electric Bain-Maries	9
	Gas Oven Bases	9
	Refrigerated / Freezer Bases	10
	Refrigerated / Freezer Bases	10
	Ambient Worktops	10
	Ambient Worktops	10
	Open Bases	11

Gas Boiling Tops without Safety Thermocouple



	169000	169001	169002	169003
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	14 5/8" (372)	14 5/8" (372)	14 5/8" (372)	14 5/8" (372)
Gas power - BTU/h	65000	130000	195000	260000
Gas power - kW	19	38	57	76
Burners - nr/BTU/h	2 x 32500	4 x 32500	6 x 32500	8 x 32500
Burners - nr/kW	2 x 9.5	4 x 9.5	6 x 9.5	8 x 9.5
ETL certification	•	•	•	•
AGA certification				
CE certification				

Gas Boiling Tops without Safety Thermocouple



	169034	169035	169036	169037
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	14 5/8" (372)	14 5/8" (372)	14 5/8" (372)	14 5/8" (372)
Gas power - BTU/h	65000	130000	195000	260000
Gas power - kW	19	38	57	76
Burners - nr/BTU/h	2 x 32500	4 x 32500	6 x 32500	8 x 32500
Burners - nr/kW	2 x 9.5	4 x 9.5	6 x 9.5	8 x 9.5
Burners safety thermocouple	•	•	•	•
ETL certification	•	•	•	•
AGA certification	•	•	•	•
CE certification				

Gas Ranges



	169004	169005	169038	169039
External dim. - inch (mm)				
width	24" (610)	36" (915)	24" (610)	36" (915)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	37 3/16" (945)	37 3/16" (945)	37 3/16" (945)	37 3/16" (945)
Gas power - BTU/h	164000	229000	164000	229000
Gas power - kW	48	67	48	67
Burners - nr/BTU/h	4 x 32500	6 x 32500	4 x 32500	6 x 32500
Burners - nr/kW	4 x 9.5	6 x 9.5	4 x 9.5	6 x 9.5
Static Oven	•	•	•	•
Burners safety thermocouple			•	•
ETL certification	•	•	•	•
AGA certification				
CE certification				

Gas Ranges



	169075	169076
External dim. - inch (mm)		
width	24" (610)	36" (915)
depth	31 1/2" (800)	31 1/2" (800)
height	37 3/16" (945)	37 3/16" (945)
Gas power - BTU/h	156000	216900
Gas power - kW	45.6	63.4
Burners - nr/BTU/h	4 x 30450	6 x 30450
Burners - nr/kW	4 x 8.9	6 x 8.9
Static Oven	•	•
Burners safety thermocouple	•	•
ETL certification		
AGA certification	•	•
CE certification		

Induction Cooking Tops 

	169007
External dim. - inch (mm)	
width	16" (406)
depth	31 1/2" (800)
height	14 5/8" (372)
Electric power - kW	7
Zones - nr/kW	2x3.5
Electric Power Supply	200-240V 1 50-60Hz
ETL certification	•
CE certification	
CB/IEC certification	

Gas French (Solid) Tops 

	169009
External dim. - inch (mm)	
width	36" (915)
depth	31 1/2" (800)
height	14 5/8" (372)
Gas power - BTU/h	27000
Gas power - kW	8
ETL certification	•
AGA certification	•
CE certification	

Smooth Gas Griddles without Piezo Ignition



	169012	169013	169014	169015
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)
Gas power - BTU/h	26000	52000	78000	104000
Gas power - kW	7.6	15.2	22.8	30.4
Smooth plate	•	•	•	•
Mild steel plate	•	•	•	•
Thermostatic Control	•	•	•	•
ETL certification	•	•	•	•
AGA certification				
CE certification				

Ribbed Gas Griddles without Piezo Ignition



	169016	169017	169018	169019
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)
Gas power - BTU/h	26000	52000	78000	104000
Gas power - kW	7.6	15.2	22.8	30.4
1/3 Ribbed plate		•	•	•
Ribbed plate	•			
Mild steel plate	•	•	•	•
Thermostatic Control	•	•	•	•
ETL certification	•	•	•	•
AGA certification				
CE certification				

Smooth Gas Griddles without Piezo Ignition



	169050	169051	169052	169053
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)
Gas power - BTU/h	22160	44320	66480	88640
Gas power - kW	6.5	13	19.5	26
Smooth plate	•	•	•	•
Mild steel plate	•	•	•	•
Thermostatic Control	•	•	•	•
ETL certification				
AGA certification	•	•	•	•
CE certification	•	•	•	•

Ribbed Gas Griddles without Piezo Ignition



	169054	169055	169056	169057
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)
Gas power - BTU/h	22160	44320	66480	88640
Gas power - kW	6.5	13	19.5	26
1/3 Ribbed plate			•	•
Ribbed plate	•			
Mild steel plate	•	•	•	•
Thermostatic Control	•	•	•	•
ETL certification				
AGA certification	•	•	•	•
CE certification	•	•	•	•

Smooth Gas Griddles with Piezo Ignition



	169067	169068	169069
External dim. - inch (mm)			
width	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)
Gas power - BTU/h	44320	66480	88640
Gas power - kW	13	19.5	26
Smooth plate	•	•	•
Mild steel plate	•	•	•
Thermostatic Control	•	•	•
Piezo ignition	•	•	•
ETL certification			
AGA certification			
CE certification	•	•	•

Ribbed Gas Griddles with Piezo Ignition



	169070	169071	169072	169073	169074
External dim. - inch (mm)					
width	24" (610)	36" (915)	48" (1220)	24" (610)	36" (915)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)	16 1/2" (419)
Gas power - BTU/h	44320	66480	88640	44320	66480
Gas power - kW	13	19.5	26	13	19.5
1/2 ribbed plate	•	•	•		
Ribbed plate				•	•
Mild steel plate	•	•	•	•	•
Thermostatic Control	•	•	•	•	•
Piezo ignition	•	•	•	•	•
ETL certification					
AGA certification					
CE certification	•	•	•	•	•

Gas Charbroilers



	169020	169021	169022	169023
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	18 3/8" (467)	18 3/8" (467)	18 3/8" (467)	18 3/8" (467)
Gas power - BTU/h	33000	66000	99000	132000
Gas power - kW	9.6	19.3	28.9	38.6
ETL certification	•	•	•	•
AGA certification				
CE certification				

Gas Charbroilers



	169058	169059	169060	169061
External dim. - inch (mm)				
width	12" (305)	24" (610)	36" (915)	48" (1220)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	18 3/8" (467)	18 3/8" (467)	18 3/8" (467)	18 3/8" (467)
Gas power - BTU/h	28980	57960	86930	115900
Gas power - kW	8.5	17	25.5	34
ETL certification				
AGA certification	•	•	•	•
CE certification	•	•	•	•

Gas Fryers



	169010	169044
External dim. - inch (mm)		
width	16" (406)	16" (406)
depth	31 1/2" (800)	31 1/2" (800)
height	47 1/4" (1200)	47 1/4" (1200)
Gas power - BTU/h	85000	85000
Gas power - kW	25	25
Wells - nr/capacity	1x40lbs/23lit	1x40lbs/23lit
Baskets - nr	2	2
ETL certification	•	
AGA certification		•
CE certification		

Gas Pastacookers



	169024
External dim. - inch (mm)	
width	16 16" (406)
depth	31 1/2" (800)
height	37 3/16" (945)
Gas power - BTU/h	42500
Gas power - kW	12.5
Wells - nr/capacity	1x6.5gal/24.5 lit
Baskets - nr	2
ETL certification	•
AGA certification	•
CE certification	

Electric Bain-Maries



	169027
External dim. - inch (mm)	
width	16" (406)
depth	31 1/2" (800)
height	14 5/8" (372)
Electric power - kW	1.5
Well capacity	GN1/1
Electrical connection	120V 1 50/60Hz
ETL certification	•
CE certification	
CB/IEC certification	

Gas Oven Bases



	169062	169011
External dim. - inch (mm)		
width	36" (915)	36" (915)
depth	31 3/2" (807)	31 3/2" (807)
height	35 3/8" (898)	35 3/8" (898)
Gas power - BTU/h	34000	41000
Gas power - kW	10	12
Static oven	•	
Convection oven		•
ETL certification	•	•
AGA certification		
CE certification		

Refrigerated / Freezer Bases 

	727094	727093	727092	727091
External dim. - inch (mm)				
width	36" (913)	48" (1218)	72" (1826)	84" (2131)
depth	32 1/64" (813)	32 1/64" (813)	32 1/64" (813)	32 1/64" (813)
height	26 3/4" (680)	26 3/4" (680)	26 3/4" (680)	26 3/4" (680)
Electric power - hp	1	1 1/2	2 1/2	2 2/3
Electric power - kW	0.7	1.15	1.83	1.95
Drawers - nr	2	2	4	4
Temperature - °C	-22 / +8	-22 / +8	-22 / +8	-22 / +8
Electrical connection	120V 1 60Hz	120V 1 60Hz	120V 1 60Hz	120V 1 60Hz
ETL certification	•	•	•	•
CE certification				

Refrigerated / Freezer Bases



	727188	727189	727190	727191
External dim. - inch (mm)				
width	36" (913)	48" (1218)	72" (1826)	84" (2131)
depth	32 1/64" (813)	32 1/64" (813)	32 1/64" (813)	32 1/64" (813)
height	26 3/4" (680)	26 3/4" (680)	26 3/4" (680)	26 3/4" (680)
Electric power - kW	0.67	0.76	1.26	1.29
Drawers - nr	2	2	4	4
Temperature - °C	-22 / +8	-22 / +8	-22 / +8	-22 / +8
Electrical connection	230V 1 50Hz	230V 1 50Hz	230V 1 50Hz	230V 1 50Hz
ETL certification				
CE certification	•	•	•	•
CB/IEC certification	•	•	•	•

Ambient Worktops 

	169033	169043	169063	169064
External dim. - inch (mm)				
width	4" (101.5)	8" (203)	12" (305)	16" (406)
depth	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)	31 1/2" (800)
height	10 5/16" (262)	10 5/16" (262)	14 1/2" (368)	14 1/2" (368)

Ambient Worktops 

	169065	169066
External dim. - inch (mm)		
width	24" (610)	36" (915)
depth	31 1/2" (800)	31 1/2" (800)
height	14 1/2" (368)	14 1/2" (368)

Open Bases



	169028	169029	169030	169031
External dim. - inch (mm)				
width	12" (305)	16" (406)	24" (610)	36" (915)
depth	29 ¹⁵ / ₁₆ " (760)	29 ¹⁵ / ₁₆ " (760)	29 ¹⁵ / ₁₆ " (760)	29 ¹⁵ / ₁₆ " (760)
height	26 ¹¹ / ₁₆ " (678)	26 ¹¹ / ₁₆ " (678)	26 ¹¹ / ₁₆ " (678)	26 ¹¹ / ₁₆ " (678)

www.electroluxusa.com/professional

Share more of our thinking at www.electrolux.com/professional

Electrolux Professional Inc.

North American Headquarters
10200 David Taylor Drive
Charlotte, NC 28262
Phone: 1.866.449.4200
Fax: 704.547.7401

Excellence with the environment in mind

Electrolux Professional solutions perfectly match the customers' needs, including the areas of reliability, cost efficiency and sustainability. The products are the best in terms of quality – durability with low running costs. Some installations have been running for more than 40 years!

- All Electrolux Professional factories are ISO 14001-certified
- All Electrolux Professional solutions are designed for low water, energy and detergent consumption, and for low emissions into the environment
- All Electrolux Professional solutions are the best-in-class in terms of quality, for a long life cycle with the lowest life cycle costs. There are solutions still running after 40 years
- All Electrolux Professional solutions are ROHS and REACH-compliant and over 95% recyclable
- All Electrolux Professional solutions are 100% quality tested and all of the functions are singularly checked by expert technicians
- In the last five years, more than 70% of Electrolux Professional solutions have been updated with features that are always designed with the needs of customers and environmental considerations in mind
- Electrolux Professional sustains a specific energy saving program to reduce the energy consumption of its production plants

