

Tabel-Top-Model EST 20 Series

Vacuum-Packing-Machines

Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



EST 20 LC



EST 20 KLS with dome lid (K)

Technical Data		EST 20 / EST 20 K
■ Chamber size inside	height depth width	155 mm 225 mm 420 mm 410 mm
■ External dimensions	height depth width	390 mm 450 mm 580 mm 465 mm
■ Weight		70 kg
■ Length of sealing bar		405 mm
■ Packaging performance		1 to 2 / min.
■ Vacuum pump standard		21 m ³ / h
■ Electrical supply standard		LC: 230V/ 1 or on request LS: 400V/ 3 or on request

Technical modifications reserved