

thermaline
ProThermetic S
Range overview



Thinking of you
Electrolux

therma*line*

A new era in professional cooking



Electrolux Professional
a Swiss production
for over 100 years

ProThermetic Stationary units are available in different body height configurations:

- ◆ **H=700** (body height 700mm Hygienic)
- ◆ **H=800** (body height 800mm)

Units can be installed on:

- ◆ **Feet** (feet can be covered with optional closing stainless steel covering plinths)
- ◆ **Stainless steel plinths**
(100mm or 200mm height depending on body height)
- ◆ **On site Concrete** or stainless steel plinths
- ◆ **Wall/cantilever** configurations with optional factory supplied kit



Index

Round Boiling Pans/ Kettles

Electric - 60 lt	6
Electric - 100 lt	9
Electric - 150 lt	12
Steam - 60 lt	15
Steam - 100 lt	18
Steam - 150 lt	21

Rectangular Boiling Pans / Kettles

Electric - 80 lt	24
Electric - 300 lt	27
Steam - 80 lt	31
Steam - 300 lt	34

Rectangular Pressure Boiling Pans / Rectangular Pressure Kettles

Electric - 200 lt	38
Steam - 200 lt	40

Rectangular Pressure Boiling Pans / Rectangular Pressure Kettles

Electric - 110 lt	42
Electric - 80 lt	44
Electric - 125 lt	45

Rectangular Pressure Braising Pans / Rectangular Pressure Skillets

Electric - 80 lt	47
Electric - 110 lt	48
Electric - 125 lt	50
Electric - 170 lt	51

Electric Round Boiling Pans - 60 lt - H 700 - 800 mm Depth



	586300 PBON06EAE0	586301 PBON06EAEM	586302 PBON06RAE0	586303 PBON06RAEM
External dim. - mm				
width	700	700	700	700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans with Backsplash - 60 lt - H 700 - 800 mm Depth



	586304 PBON06EJEO	586305 PBON06EJEM	586306 PBON06RJEO	586307 PBON06RJEM
External dim. - mm				
width	700	700	700	700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans with Backsplash - 60 lt - H 800 - 800 mm Depth



	586328 PBON06EMEO	586329 PBON06EMEM	586330 PBON06RMEO	586331 PBON06RMEM
External dim. - mm				
width	700	700	700	700
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans - 60 lt - H 700 - 850 mm Depth



	586308 PBON06EBEO	586309 PBON06EBEM	586310 PBON06RBEO	586311 PBON06RBEM
External dim. - mm				
width	700	700	700	700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans with Backsplash 60 lt - H 700 - 850 mm Depth



	586312 PBON06EKEO	586313 PBON06EKEM	586314 PBON06RKEO	586315 PBON06RKEM
External dim. - mm				
width	700	700	700	700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans - 60 lt - H 700 - 900 mm Depth



	586316 PBON06ECEO	586317 PBON06ECEM	586318 PBON06RCEO	586319 PBON06RCEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans with Backsplash - 60 lt - H 700 - 900 mm Depth



	586320 PBON06ELEO	586321 PBON06ELEM	586322 PBON06RLEO	586323 PBON06RLEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans with Backsplash - 60 lt - H 800 - 900 mm Depth



	586336 PBON06EPEO	586337 PBON06EPEM	586338 PBON06RPEO	586339 PBON06RPEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans - 60 lt - H 800 - 900 mm Depth



	586332 PBON06EGEO	586333 PBON06EGEM	586334 PBON06RGEO	586335 PBON06RGEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	12	12	12,4	12,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	60	60	60	60

Electric Round Boiling Pans - 100 lt - H 700 - 800 mm Depth



	586340 PBON10EAE0	586341 PBON10EAEM	586342 PBON10RAE0	586343 PBON10RAEM
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans with Backsplash - 100 lt - H 700 - 800 mm Depth



	586344 PBON10EJEO	586345 PBON10EJEM	586346 PBON10RJEO	586347 PBON10RJEM
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans - 100 lt - H 800 - 800 mm Depth



	586364 PBON10EEEE0	586365 PBON10EEEM	586366 PBON10REE0	586367 PBON10REEM
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans with Backsplash - 100 lt - H 800 - 800 mm Depth



	586368 PBON10EMEO	586369 PBON10EMEM	586370 PBON10RMEO	586371 PBON10RMEM
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans - 100 lt - H 700 - 850 mm Depth



	586348 PBON10EBEO	586349 PBON10EBEM	586350 PBON10RBEO	586351 PBON10RBEM
External dim. - mm				
width	800	800	800	800
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans with Backsplash - 100 lt - H 700 - 850 mm Depth



	586352 PBON10EKEO	586353 PBON10EKEM	586354 PBON10RKEO	586355 PBON10RKEM
External dim. - mm				
width	800	800	800	800
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans - 100 lt - H 700 - 900 mm Depth



	586356 PBON10ECE0	586357 PBON10ECEM	586358 PBON10RCE0	586359 PBON10RCEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans with Backsplash - 100 lt - H 700 - 900 mm Depth



	586360 PBON10ELE0	586361 PBON10ELEM	586362 PBON10RLE0	586363 PBON10RLEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans - 100 lt - H 800 - 900 mm Depth



	586372 PBON10EGEO	586373 PBON10EGEM	586374 PBON10RGE0	586375 PBON10RGEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans with Backsplash - 100 lt - H 800 - 900 mm Depth



	586376 PBON10EPEO	586377 PBON10EPEM	586378 PBON10RPEO	586379 PBON10RPEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	18	18	18,4	18,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100

Electric Round Boiling Pans - 150 lt - H 700 - 850 mm Depth



	586380 PBON10RPEM	586381 PBON15EBEM	586382 PBON15RBEO	586383 PBON15RBEM
External dim. - mm				
width	900	800	800	800
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	24	24	24,4	24,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	150	150	150	150

Electric Round Boiling Pans with Backsplash - 150 lt - H 700 - 850 mm Depth



	586384 PBON15EKEO	586385 PBON15EKEM	586386 PBON15RKEO	586387 PBON15RKEM
External dim. - mm				
width	900	900	900	900
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	24	24	24,4	24,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	150	150	150	150

Electric Round Boiling Pans - 150 lt - H 700 - 900 mm Depth



	586388 PBON15ECE0	586389 PBON15ECEM	586390 PBON15RCE0	586391 PBON15RCEM
External dim. - mm				
width	900	900	900	900
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	24	24	24,4	24,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	150	150	150	150

Electric Round Boiling Pans with Backsplash - 150 lt - H 700 - 900 mm Depth



	586392 PBON15ELE0	586393 PBON15ELEM	586394 PBON15RLE0	586395 PBON15RLEM
External dim. - mm				
width	900	900	900	900
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	24	24	24,4	24,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	150	150	150	150

Electric Round Boiling Pans - 150 lt - H 800 - 900 mm Depth



	586396 PBON15EGEO	586397 PBON15EGEM	586398 PBON15RGEO	586399 PBON15RGEM
External dim. - mm				
width	900	900	900	900
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	24	24	24,4	24,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	150	150	150	150

Electric Round Boiling Pans with Backsplash - 150 lt - H 800 - 900 mm Depth



	586400 PBON15EPEO	586401 PBON15EPEM	586402 PBON15RPEO	586403 PBON15RPEM
External dim. - mm				
width	900	900	900	900
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	24	24	24,4	24,4
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	150	150	150	150

Steam Round Boiling Pans - 60 lt - H 700 - 800 mm Depth



	586404 PBON06SACO	586405 PBON06SACM	586406 PBON06QAEO	586407 PBON06QAEM
External dim. - mm				
width	700	700	700	700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans with Backsplash - 60 lt - H 700 - 800 mm Depth



	586408 PBON06SJCO	586409 PBON06SJCM	586410 PBON06QJEO	586411 PBON06QJEM
External dim. - mm				
width	700	700	700	700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans - 60 lt - H 800 - 800 mm Depth



	586428 PBON06SECO	586429 PBON06SECM	586430 PBON06QEEO	586431 PBON06QEEM
External dim. - mm				
width	700	700	700	700
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans with Backsplash - 60 lt - H 800 - 800 mm Depth



	586432 PBON06SMCO	586433 PBON06SMCM	586434 PBON06QMEO	586435 PBON06QMEM
External dim. - mm				
width	700	700	700	700
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans - 60 lt - H 700 - 850 mm Depth



	586412 PBON06SBCO	586413 PBON06SBCM	586414 PBON06QBEO	586415 PBON06QBEM
External dim. - mm				
width	700	700	700	700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans with Backsplash - 60 lt - H 700 - 850 mm Depth



	586416 PBON06SKCO	586417 PBON06SKCM	586418 PBON06QKEO	586419 PBON06QKEM
External dim. - mm				
width	700	700	700	700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans - 60 lt - H 700 - 900 mm Depth



	586420 PBON06SCCO	586421 PBON06SCCM	586422 PBON06QCEO	586423 PBON06QCEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans with Backsplash - 60 lt - H 700 - 900 mm Depth



	586424 PBON06SLCO	586425 PBON06SLCM	586426 PBON06QLEO	586427 PBON06QLEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans - 60 lt - H 800 - 900 mm Depth



	586436 PBON06SGCO	586437 PBON06SGCM	586438 PBON06QGE0	586439 PBON06QGEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans with Backsplash - 60 lt - H 800 - 900 mm Depth



	586440 PBON06SPCO	586441 PBON06SPCM	586442 PBON06QPEO	586443 PBON06QPEM
External dim. - mm				
width	700	700	700	700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1556	1556	1556	1556
Electric Power - kW	0,25	0,25	0,45	0,45
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	60	60	60	60
Steam consumption - kg/h	60	60	60	60

Steam Round Boiling Pans - 100 lt - H 700 - 800 mm Depth



	586444 PBON10SACO	586445 PBON10SACM	586446 PBON10QAE0	586447 PBON10QAE M
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans with Backsplash - 100 lt - H 700 - 800 mm Depth



	586448 PBON10SJCO	586449 PBON10SJCM	586450 PBON10QJEO	586451 PBON10QJEM
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans - 100 lt - H 800 - 800 mm Depth



Steam round boiling pans*	586468 PBON10SECO	586469 PBON10SECM	586470 PBON10QEEO	586471 PBON10QEEM
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans with Backsplash - 100 lt - H 800 - 800 mm Depth



	586472 PBON10SMCO	586473 PBON10SMCM	586474 PBON10QMEO	586475 PBON10QMCM
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans - 100 lt - H 700 - 850 mm Depth



	586452 PBON10SBCO	586453 PBON10SBCM	586454 PBON10QBEO	586455 PBON10QBEM
External dim. - mm				
width	800	800	800	800
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans with Backsplash - 100 lt - H 700 - 850 mm Depth



	586456 PBON10SKCO	586457 PBON10SKCM	586458 PBON10QKEO	586459 PBON10QKEM
External dim. - mm				
width	800	800	800	800
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57v
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans - 100 lt - H 700 - 900 mm Depth



	586460 PBON10SCCO	586461 PBON10SCCM	586462 PBON10QCEO	586463 PBON10QCEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans with Backsplash - 100 lt - H 700 - 900 mm Depth



	586464 PBON10SLCO	586465 PBON10SLCM	586466 PBON10QLEO	586467 PBON10QLEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans - 100 lt - H 800 - 900 mm Depth



	586476 PBON10SGCO	586477 PBON10SGCM	586478 PBON10QGEO	586479 PBON10QGEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans with Backsplash - 100 lt - H 800 - 900 mm Depth



	586480 PBON10SPCO	586481 PBON10SPCM	586482 PBON10QPEO	586483 PBON10QPEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1647	1647	1647	1647
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	100	100	100	100
Steam consumption - kg/h	80	80	80	80

Steam Round Boiling Pans - 150 lt - H 700 - 850 mm Depth



	586484 PBON15SBCO	586485 PBON15SBCM	586486 PBON15QBEO	586487 PBON15QBEM
External dim. - mm				
width	900	900	900	900
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	150	150	150	150
Steam consumption - kg/h	100	100	100	100

Steam Round Boiling Pans with Backsplash - 150 lt - H 700 - 850 mm Depth



	586488 PBON15SKCO	586489 PBON15SKCM	586490 PBON15QKEO	586491 PBON15QKEM
External dim. - mm				
width	900	900	900	900
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	0,25	0,25	0,57	0,57v
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	150	150	150	150
Steam consumption - kg/h	100	100	100	100

Steam Round Boiling Pans - 150 lt - H 700 - 900 mm Depth



	586492 PBON15SCCO	586493 PBON15SCCM	586494 PBON15QCEO	586495 PBON15QCEM
External dim. - mm				
width	900	900	900	900
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Well capacity - lt	150	150	150	150
Steam consumption - kg/h	100	100	100	100

Steam Round Boiling Pans with Backsplash - 150 lt - H 700 - 900 mm Depth



	586496 PBON15SLCO	586497 PBON15SLCM	586498 PBON15QLEO	586499 PBON15QLEM
External dim. - mm				
width	800	800	800	800
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	150	150	150	150
Steam consumption - kg/h	100	100	100	100

Steam Round Boiling Pans - 150 lt - H 800 - 900 mm Depth



	586500 PBON15SGCO	586501 PBON15SGCM	586502 PBON15QGEO	586503 PBON15QGEM
External dim. - mm				
width	900	900	900	900
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Well capacity - lt	150	150	150	150
Steam consumption - kg/h	100	100	100	100

Steam Round Boiling Pans with Backsplash - 150 lt - H 800 - 900 mm Depth



	586504 PBON15SPCO	586505 PBON15SPCM	586506 PBON15QPEO	586507 PBON15QPEM
External dim. - mm				
width	900	900	900	900
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1701	1701	1701	1701
Electric Power - kW	0,25	0,25	0,57	0,57
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		
Stirrer			•	
Stirrer & mixing tap				•
Wall mounted	•	•	•	•
Well capacity - lt	150	150	150	150
Steam consumption - kg/h	100	100	100	100

Electric Rectangular Boiling Pans - 80 lt - H 700 - 800 mm Depth



	586508 PBEN08EAEO	586509 PBEN08EAEM	586528 PBEN20EAEO	586529 PBEN20EAEM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans with Backsplash - 80 lt - H 700 - 800 mm Depth



	586510 PBEN08EJEO	586511 PBEN08EJEM	586530 PBEN20EJEO	586531 PBEN20EJEM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans - 80 lt - H 800 - 800 mm Depth



	586520 PBEN08EEEEEO	586521 PBEN08EEEEEM	586540 PBEN20EEEEEO	586541 PBEN20EEEEEM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans with Backsplash - 80 lt - H 800 - 800 mm Depth



	586522 PBEN08EMEO	586523 PBEN08EMEM	586542 PBEN20EMEO	586543 PBEN20EMEM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans - 80 lt - H 700 - 850 mm Depth



	586512 PBEN08EBEO	586513 PBEN08EBEM	586532 PBEN20EBEO	586533 PBEN20EBEM
External dim. - mm				
width	700	700	1000	1000
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans with Backsplash - 80 lt - H 700 - 850 mm Depth



	586514 PBEN08EKEO	586515 PBEN08EKEM	586534 PBEN20EKEO	586535 PBEN20EKEM
External dim. - mm				
width	700	700	1000	1000
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans - 80 lt - H 700 - 900 mm Depth



	586516 PBEN08ECE0	586517 PBEN08ECEM	586536 PBEN20ECE0	586537 PBEN20ECEM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans with Backsplash - 80 lt - H 700 - 900 mm Depth



	586518 PBEN08ELE0	586519 PBEN08ELEM	586538 PBEN20ELE0	586539 PBEN20ELEM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans - 80 lt - H 800 - 900 mm Depth



	586524 PBEN08EGEO	586525 PBEN08EGEM	586544 PBEN20EGEO	586545 PBEN20EGEM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans with Backsplash - 80 lt - H 800 - 900 mm Depth



	586526 PBEN08EPEO	586527 PBEN08EPEM	586546 PBEN20EPEO	586547 PBEN20EPEM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	18	18	30	30
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200

Electric Rectangular Boiling Pans - 300 lt - H 700 - 800 mm Depth



	586548 PBEN30EAE0	586549 PBEN30EAEM	586568 PBEN40EAE0	586569 PBEN40EAEM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans with Backsplash - 300 lt - H 700 - 800 mm Depth



	586550 PBEN30EJEO	586551 PBEN30EJEM	586570 PBEN40EJEO	586571 PBEN40EJEM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans - 300 lt - H 800 - 800 mm Depth



	586560 PBEN30EEEE	586561 PBEN30EEEM	586580 PBEN40EEEE	586581 PBEN40EEEM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans with Backsplash - 300 lt - H 800 - 800 mm Depth



	586562 PBEN30EMEO	586563 PBEN30EMEM	586582 PBEN40EMEO	586583 PBEN40EMEM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans - 300 lt - H 700 - 850 mm Depth



	586552 PBEN30EBEO	586553 PBEN30EBEM	586572 PBEN40EBEO	586573 PBEN40EBEM
External dim. - mm				
width	1400	1400	1700	1700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans with Backsplash - 300 lt - H 700 - 850 mm Depth



	586554 PBEN30EKEO	586555 PBEN30EKEM	586574 PBEN40EKEO	586575 PBEN40EKEM
External dim. - mm				
width	1400	1400	1700	1700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans - 300 lt - H 700 - 900 mm Depth



	586556 PBEN30ECEO	586557 PBEN30ECEM	586576 PBEN40ECEO	586577 PBEN40ECEM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans with Backsplash - 300 lt - H 800 - 900 mm Depth



	586566 PBEN30EPEO	586567 PBEN30EPEM	586586 PBEN40EPEO	586587 PBEN40EPEM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans - 300 lt - H 800 - 900 mm Depth



	586564 PBEN30EGEO	586565 PBEN30EGEM	586584 PBEN40EGEO	586585 PBEN40EGEM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	300	300	400	400

Electric Rectangular Boiling Pans with Backsplash - 300 lt - H 700 - 900 mm Depth



	586558 PBEN30ELEO	586559 PBEN30ELEM	586578 PBEN40ELEO	586579 PBEN40ELEM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	36	36	48	48
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400

Steam Rectangular Boiling Pans - 80 lt - H 700 - 800 mm Depth



	586588 PBEN08SACO	586589 PBEN08SACM	586608 PBEN20SACO	586609 PBEN20SACM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans with Backsplash - 80 lt - H 700 - 800 mm Depth



	586590 PBEN08SJCO	586591 PBEN08SJCM	586610 PBEN20SJCO	586611 PBEN20SJCM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans - 80 lt - H 800 - 800 mm Depth



	586600 PBEN08SECO	586601 PBEN08SECM	586620 PBEN20SECO	586621 PBEN20SECM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans with Backsplash - 80 lt - H 800 - 800 mm Depth



	586602 PBEN08SMCO	586603 PBEN08SMCM	586622 PBEN20SMCO	586623 PBEN20SMCM
External dim. - mm				
width	700	700	1000	1000
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans - 80 lt - H 700 - 850 mm Depth



	586592 PBEN08SBCO	586593 PBEN08SBCM	586612 PBEN20SBCO	586613 PBEN20SBCM
External dim. - mm				
width	700	700	1000	1000
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans with Backsplash - 80 lt - H 700 - 850 mm Depth



	586594 PBEN08SKCO	586595 PBEN08SKCM	586614 PBEN20SKCO	586615 PBEN20SKCM
External dim. - mm				
width	700	700	1000	1000
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans - 80 lt - H 700 - 900 mm Depth



	586596 PBEN08SCCO	586597 PBEN08SCCM	586616 PBEN20SCCO	586617 PBEN20SCCM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans with Backsplash - 80 lt - H 700 - 900 mm Depth



	586598 PBEN08SLCO	586599 PBEN08SLCM	586618 PBEN20SLCO	586619 PBEN20SLCM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans - 80 lt - H 800 - 900 mm Depth



	586604 PBEN08SGCO	586605 PBEN08SGCM	586624 PBEN20SGCO	586625 PBEN20SGCM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans with Backsplash - 80 lt - H 800 - 900 mm Depth



	586606 PBEN08SPCO	586607 PBEN08SPCM	586626 PBEN20SPCO	586627 PBEN20SPCM
External dim. - mm				
width	700	700	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	200	200
Steam consumption - kg/h			120	120

Steam Rectangular Boiling Pans - 300 lt - H 700 - 800 mm Depth



	586628 PBEN30SACO	586629 PBEN30SACM	586648 PBEN40SACO	586649 PBEN40SACM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans with Backsplash - 300 lt - H 700 - 800 mm Depth



	586630 PBEN30SJCO	586631 PBEN30SJCM	586650 PBEN40SJCO	586651 PBEN40SJCM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans - 300 lt - H 800 - 800 mm Depth



	586640 PBEN30SECO	586641 PBEN30SECM	586660 PBEN40SECO	586661 PBEN40SECM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans with Backsplash - 300 lt - H 800 - 800 mm Depth



	586642 PBEN30SMCO	586643 PBEN30SMCM	586662 PBEN40SMCO	586663 PBEN40SMCM
External dim. - mm				
width	1400	1400	1700	1700
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans - 300 lt - H 700 - 850 mm Depth



	586632 PBEN30SBCO	586633 PBEN30SBCM	586652 PBEN40SBCO	586653 PBEN40SBCM
External dim. - mm				
width	1400	1400	1700	1700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans with Backsplash - 300 lt - H 700 - 850 mm Depth



	586634 PBEN30SKCO	586635 PBEN30SKCM	586654 PBEN40SKCO	586655 PBEN40SKCM
External dim. - mm				
width	1400	1400	1700	1700
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans - 300 lt - H 700 - 900 mm Depth



	586636 PBEN30SCCO	586637 PBEN30SCCM	586656 PBEN40SCCO	586657 PBEN40SCCM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans with Backsplash - 300 lt - H 700 - 900 mm Depth



	586638 PBEN30SLCO	586639 PBEN30SLCM	586658 PBEN40SLCO	586659 PBEN40SLCM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans - 300 lt - H 800 - 900 mm Depth



	586644 PBEN30SGCO	586645 PBEN30SGCM	586664 PBEN40SGCO	586665 PBEN40SGCM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Steam Rectangular Boiling Pans with Backsplash - 300 lt - H 800 - 900 mm Depth



	586646 PBEN30SPCO	586647 PBEN30SPCM	586666 PBEN40SPCO	586667 PBEN40SPCM
External dim. - mm				
width	1400	1400	1700	1700
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1731	1731	1731	1731
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	300	300	400	400
Steam consumption - kg/h	130	130	118	118

Electric Rectangular Pressure Boiling Pans - 200 lt - H 700 - 850 mm Depth



	586668 PPEN20EBEO	586669 PPEN20EBEM	586680 PPEN30EBEO	586681 PPEN30EBEM
External dim. - mm				
width	1000	1000	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	30	30	36	36
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	200	200	300	300

Electric Rectangular Pressure Boiling Pans with Backsplash - 200 lt - H 700 - 850 mm Depth



	586670 PPEN20EKEO	586671 PPEN20EKEM	586682 PPEN30EKEO	586683 PPEN30EKEM
External dim. - mm				
width	1000	1000	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	30	30	36	36
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	200	200	300	300

Electric Rectangular Pressure Boiling Pans - 200 lt - H 700 - 900 mm Depth



	586672 PPEN20ECE0	586673 PPEN20ECEM	586684 PPEN30ECE0	586685 PPEN30ECEM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	30	30	36	36
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	200	200	300	300

Electric Rectangular Pressure Boiling Pans with Backsplash - 200 lt - H 700 - 900 mm Depth



	586674 PPEN20ELEO	586675 PPEN20ELEM	586686 PPEN30ELEO	586687 PPEN30ELEM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	30	30	36	36
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	200	200	300	300

Electric Rectangular Pressure Boiling Pans - 200 lt - H 800 - 900 mm Depth



	586676 PPEN20EGEO	586677 PPEN20EGEM	586688 PPEN30EGEO	586689 PPEN30EGEM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	30	30	36	36
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	200	200	300	300

Electric Rectangular Pressure Boiling Pans with Backsplash - 200 lt - H 800 - 900 mm Depth



	586678 PPEN20EPEO	586679 PPEN20EPEM	586690 PPEN30EPEO	586691 PPEN30EPEM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	30	30	36	36
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	200	200	300	300

Steam Rectangular Pressure Boiling Pans - 200 lt - H 700 - 850 mm Depth



	586692 PPEN20SBCO	586693 PPEN20SBCM	586704 PPEN30SBCO	586705 PPEN30SBCM
External dim. - mm				
width	1000	1000	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	200	200	300	300
Steam consumption - kg/h	120	120	130	130

Steam Rectangular Pressure Boiling Pans with Backsplash - 200 lt - H 700 - 850 mm Depth



	586694 PPEN20SKCO	586695 PPEN20SKCM	586706 PPEN30SKCO	586707 PPEN30SKCM
External dim. - mm				
width	1000	1000	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	200	200	300	300
Steam consumption - kg/h	120	120	130	130

Steam Rectangular Pressure Boiling Pans - 200 lt - H 700 - 900 mm Depth



	586696 PPEN20SCCO	586697 PPEN20SCCM	586708 PPEN30SCCO	586709 PPEN30SCCM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	200	200	300	300
Steam consumption - kg/h	120	120	130	130

Steam Rectangular Pressure Boiling Pans with Backsplash - 200 lt - H 700 - 900 mm Depth



	586698 PPEN20SLCO	586699 PPEN20SLCM	586710 PPEN30SLCO	586711 PPEN30SLCM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	200	200	300	300
Steam consumption - kg/h	120	120	130	130

Steam Rectangular Pressure Boiling Pans - 200 lt - H 800 - 900 mm Depth



	586700 PPEN20SGCO	586701 PPEN20SGCM	586712 PPEN30SGCO	586713 PPEN30SGCM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	200	200	300	300
Steam consumption - kg/h	120	120	130	130

Steam Rectangular Pressure Boiling Pans with Backsplash - 200 lt - H 800 - 900 mm Depth



	586702 PPEN20SPCO	586703 PPEN20SPCM	586714 PPEN30SPCO	586715 PPEN30SPCM
External dim. - mm				
width	1000	1000	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	0,25	0,25	0,25	0,25
Electrical connection	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz	230V 1N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	200	200	300	300
Steam consumption - kg/h	120	120	130	130

Electric Rectangular Braising Pans - 110 lt - H 700 - 800 mm Depth



	586724 PFEN11EAE0	586725 PFEN11EAEM	586752 PFEN17EAE0	586753 PFEN17EAEM
External dim. - mm				
width	1000	1000	1400	1400
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1730	1730	1730	1730
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	110	110	170	170

Electric Rectangular Braising Pans with Backsplash - 110 lt - H 700 - 800 mm Depth



	586726 PFEN11EJEO	586727 PFEN11EJEM	586754 PFEN17EJEO	586755 PFEN17EJEM
External dim. - mm				
width	1000	1000	1400	1400
depth	800	800	800	800
height	700	700	700	700
overall height (lid open)	1730	1730	1730	1730
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	110	110	170	170

Electric Rectangular Braising Pans - 110 lt - H 800 - 800 mm Depth



	586736 PFEN11EEEE0	586737 PFEN11EEEM	586764 PFEN17EEEE0	586765 PFEN17EEEM
External dim. - mm				
width	1000	1000	1400	1400
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1730	1730	1730	1730
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	110	110	170	170

Electric Rectangular Braising Pans with Backsplash - 110 lt - H 800 - 800 mm Depth



	586738 PFEN11EMEO	586739 PFEN11EMEM	586766 PFEN17EMEO	586767 PFEN17EMEM
External dim. - mm				
width	1000	1000	1400	1400
depth	800	800	800	800
height	800	800	800	800
overall height (lid open)	1730	1730	1730	1730
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	110	110	170	170

Electric Rectangular Braising Pans - 110 lt - H 700 - 850 mm Depth



	586728 PFEN11EBEO	586729 PFEN11EBEM	586756 PFEN17EBEO	586757 PFEN17EBEM
External dim. - mm				
width	1000	1000	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1730	1730	1730	1730
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	110	110	170	170

Electric Rectangular Braising Pans with Backsplash - 110 lt - H 700 - 850 mm Depth



	586730 PFEN11EKEO	586731 PFEN11EKEM	586758 PFEN17EKEO	586759 PFEN17EKEM
External dim. - mm				
width	1000	1000	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1730	1730	1730	1730
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	110	110	170	170

Electric Rectangular Braising Pans - 80 lt - H 700 - 900 mm Depth



	586716 PFEN08ECEC	586717 PFEN08ECEM	586732 PFEN11ECEC	586733 PFEN11ECEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1717	1717	1717	1717
Electric Power - kW	12,2	12,2	15,5	15,5
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	110	110

Electric Rectangular Braising Pans with Backsplash - 80 lt - H 700 - 900 mm Depth



	586718 PFEN08ELEO	586719 PFEN08ELEM	586734 PFEN11ELEO	586735 PFEN11ELEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1717	1717	1717	1717
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	110	110

Electric Rectangular Braising Pans - 80 lt - H 800 - 900 mm Depth



	586720 PFEN08EGEO	586721 PFEN08EGEM	586740 PFEN11EGEO	586741 PFEN11EGEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1717	1717	1717	1717
Electric Power - kW	12,2	12,2	15,5	15,5
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	80	80	110	110

Electric Rectangular Braising Pans with Backsplash - 80 lt - H 800 - 900 mm Depth



	586722 PFEN08EPEO	586723 PFEN08EPEM	586742 PFEN11EPEO	586743 PFEN11EPEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1717	1717	1717	1717
Electric Power - kW	12,2	12,2	15,5	15,5
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	110	110

Electric Rectangular Braising Pans - 125 lt - H 700 - 900 mm Depth



	586744 PFEN12ECEO	586745 PFEN12ECEM	586760 PFEN17ECEO	586761 PFEN17ECEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1718	1718	1718	1718
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	125	125	170	170

Electric Rectangular Braising Pans with Backsplash - 125 lt - H 700 - 900 mm Depth



	586746 PFEN12ELEO	586747 PFEN12ELEM	586762 PFEN17ELEO	586763 PFEN17ELEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1718	1718	1718	1718
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	125	125	170	170

Electric Rectangular Braising Pans - 125 lt - H 800 - 900 mm Depth



	586748 PFEN12EGEO	586749 PFEN12EGEM	586768 PFEN17EGEO	586769 PFEN17EGEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1718	1718	1718	1718
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Well capacity - lt	125	125	170	170

Electric Rectangular Braising Pans with Backsplash - 125 lt - H 800 - 900 mm Depth



	586750 PFEN12EPEO	586751 PFEN12EPEM	586770 PFEN17EPEO	586771 PFEN17EPEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1718	1718	1718	1718
Electric Power - kW	15,5	15,5	20,6	20,6
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	125	125	170	170

Electric Rectangular Pressure Braising Pans - 80 lt - H 700 - 900 mm Depth



	586772 PUEN08ECE0	586773 PUEN08ECEM	586776 PUEN08KCE0	586777 PUEN08KCEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1818	1818	1818	1818
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	80	80	80	80

Electric Rectangular Pressure Braising Pans with Backsplash - 80 lt - H 700 - 900 mm Depth



	586774 PUEN08ELE0	586775 PUEN08ELEM	586778 PUEN08KLE0	586779 PUEN08KLEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1818	1818	1818	1818
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	80	80

Electric Rectangular Pressure Braising Pans - 80 lt - H 800 - 900 mm Depth



	586780 PUEN08EGEO	586781 PUEN08EGEM	586784 PUEN08KGEO	586785 PUEN08KSEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1818	1818	1818	1818
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Well capacity - lt	80	80	80	80

Electric Rectangular Pressure Braising Pans with Backsplash - 80 lt - H 800 - 900 mm Depth



	586782 PUEN08EPEO	586783 PUEN08EPEM	586786 PUEN08KPEO	586787 PUEN08KPEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1818	1818	1818	1818
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	80	80	80	80

Electric Rectangular Pressure Braising Pans - 110 lt - H 700 - 850 mm Depth



	586788 PUEN11EBEO	586789 PUEN11EBEM	586792 PUEN11KBEO	586793 PUEN11KBEM
External dim. - mm				
width	1000	1000	1000	1000
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1820	1820	1820	1820
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	110	110	110	110

Electric Rectangular Pressure Braising Pans with Backsplash - 110 lt - H 700 - 850 mm Depth



	586790 PUEN11EKEO	586791 PUEN11EKEM	586794 PUEN11KKEO	586795 PUEN11KKEM
External dim. - mm				
width	1000	1000	1000	1000
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1820	1820	1820	1820
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	110	110	110	110

Electric Rectangular Pressure Braising Pans - 110 lt - H 700 - 900 mm Depth



	586796 PUEN11ECE0	586797 PUEN11ECEM	586800 PUEN11KCE0	586801 PUEN11KCEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1820	1820	1820	1820
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	110	110	110	110

Electric Rectangular Pressure Braising Pans with Backsplash - 110 lt - H 700 - 900 mm Depth



	586798 PUEN11ELE0	586799 PUEN11ELEM	586802 PUEN11KLE0	586803 PUEN11KLEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1820	1820	1820	1820
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	110	110	110	110

Electric Rectangular Pressure Braising Pans - 110 lt - H 800 - 900 mm Depth



	586804 PUEN11EGEO	586805 PUEN11EGEM	586808 PUEN11KGEO	586809 PUEN11KGEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1820	1820	1820	1820
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Well capacity - lt	110	110	110	110

Electric Rectangular Pressure Braising Pans with Backsplash - 110 lt - H 800 - 900 mm Depth



	586806 PUEN11EPEO	586807 PUEN11EPEM	586810 PUEN11KPEO	586811 PUEN11KPEM
External dim. - mm				
width	1000	1000	1000	1000
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1820	1820	1820	1820
Electric Power - kW	12,2	12,2	12,2	12,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	110	110	110	110

Electric Rectangular Pressure Braising Pans - 125 lt - H 700 - 850 mm Depth



	586812 PUEN12ECEO	586813 PUEN12ECEM	586816 PUEN12KCEO	586817 PUEN12KCEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	125	125	125	125

Electric Rectangular Pressure Braising Pans with Backsplash - 125 lt - H 700 - 900 mm Depth



	586814 PUEN12ELEO	586815 PUEN12ELEM	586818 PUEN12KLEO	586819 PUEN12KLEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	125	125	125	125

Electric Rectangular Pressure Braising Pans - 125 lt - H 800 - 900 mm Depth



	586820 PUEN12EGEO	586821 PUEN12EGEM	586824 PUEN12KGEO	586825 PUEN12KSEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Well capacity - lt	125	125	125	125

Electric Rectangular Pressure Braising Pans with Backsplash - 125 lt - H 800 - 900 mm Depth



	586822 PUEN12EPEO	586823 PUEN12EPEM	586826 PUEN12KPEO	586827 PUEN12KPEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	125	125	125	125

Electric Rectangular Pressure Braising Pans - 170 lt - H 700 - 850 mm Depth



	586828 PUEN17EBEO	586829 PUEN17EBEM	586832 PUEN17KBEO	586833 PUEN17KBEM
External dim. - mm				
width	1400	1400	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	170	170	170	170

Electric Rectangular Pressure Braising Pans with Backsplash - 170 lt - H 700 - 850 mm Depth



	586830 PUEN17EKEO	586831 PUEN17EKEM	586834 PUEN17KKEO	586835 PUEN17KKEM
External dim. - mm				
width	1400	1400	1400	1400
depth	850	850	850	850
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	170	170	170	170

Electric Rectangular Pressure Braising Pans - 170 lt - H 700 - 900 mm Depth



	586836 PUEN17ECE0	586837 PUEN17ECEM	586840 PUEN17KCE0	586841 PUEN17KCEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Well capacity - lt	170	170	170	170

Electric Rectangular Pressure Braising Pans with Backsplash - 170 lt - H 700 - 900 mm Depth



	586838 PUEN17ELE0	586839 PUEN17ELEM	586842 PUEN17KLE0	586843 PUEN17KLEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	700	700	700	700
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Hygienic plinth	•	•	•	•
Wall mounted	•	•	•	•
Well capacity - lt	170	170	170	170

Electric Rectangular Pressure Braising Pans - 170 lt - H 800 - 900 mm Depth



	586844 PUEN17EGEO	586845 PUEN17EGEM	586848 PUEN17KGEO	586849 PUEN17KSEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Well capacity - lt	170	170	170	170

Electric Rectangular Pressure Braising Pans with Backsplash - 170 lt - H 800 - 900 mm Depth



	586846 PUEN17EPEO	586847 PUEN17EPEM	586850 PUEN17KPEO	586851 PUEN17KPEM
External dim. - mm				
width	1400	1400	1400	1400
depth	900	900	900	900
height	800	800	800	800
overall height (lid open)	1819	1819	1819	1819
Electric Power - kW	18,2	18,2	18,2	18,2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Core temperature sensor			•	•
Mixing tap		•		•
Wall mounted	•	•	•	•
Well capacity - lt	170	170	170	170

www.electrolux.com/foodservice

Share more of our thinking at www.electrolux.com