



 **therma***line*

Modular 80

**Range Overview**



*Thinking of you*  
**Electrolux**

# thermaline: Swiss excellence

a new era in professional cooking



**1871** Production, Precision  
and Tradition

for over 100 years



### Full flexible modular cooking line made composed of:

#### ◆ Top units

- H=250

#### ◆ Stand alone units

- H=700 (body height 700mm Hygienic)
- H=800 (body height 800mm)

#### ◆ Bases

- (for installation of top units)
- H=450 (for total body height including top of 700mm hygienic)
- H=550 (for total body height of 800mm)

### Units can be found in various installation Operating Side configurations:

- ◆ **Stand alone one side island operation**  
(control panel found on one side)
- ◆ **Stand alone two side island operation**  
(control panel found on both side of the units)
- ◆ **Stand alone one side against the wall operation** (control panel on one side with backsplash on rear of the unit)

### Units can be installed on:

- ◆ **Feet** (feet can be covered with optional closing stainless steel covering plinths)
- ◆ **Stainless steel plinths**  
(100mm or 200mm height)
- ◆ **On site Concrete** or stainless steel plinths
- ◆ **Wall/cantilever** configurations with optional factory supplied kit (verify with factory possible configurations certain units)

## Index

Electric Solid Tops - 2 Zones	6
Electric Solid Tops - 2 Zones - Freestanding - H 700 mm	6
Electric Solid Tops - 2 Zones - Freestanding - H 800 mm	6
Electric Solid Tops - 4 Zones	6
Electric Solid Tops - 4 Zones - Freestanding - H 700 mm	7
Electric Solid Tops - 4 Zones - Freestanding - H 800 mm	7
Infrared Tops - 2 and 4 Zones	7
Induction Tops - 2 Zones	7
Induction Tops - 4 Zones	8
Induction Woks	8
Gas Burner Tops - 2 Burners	8
Gas Burner Tops - 4 and 6 Burners	8
Gas Burner Tops - 2 Burners - Ecoflam	9
Gas Burner Tops - 4 and 6 Burners - Ecoflam	9
Electric Fry Tops - Smooth Chrome Plate	9
Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 700 mm	9
Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 800 mm	10
Electric Fry Tops - Ribbed Chrome Plate	10
Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 700 mm	10
Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 800 mm	10
Electric Fry Tops - Smooth and Ribbed Chrome Plate	11
Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 700 mm	11
Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 800 mm	11
Electric Free-cooking Tops	11
Electric Free-cooking Tops - Freestanding - H 700 mm	12
Electric Free-cooking Tops - Freestanding - H 800 mm	12
Electric Bain Marie Tops	12
Electric Aquacookers - Freestanding - H 700 m	13
Electric Aquacookers - Freestanding - H 800 mm	13
Electric Multi Braisers - 1/1 GN - Freestanding - H 700 mm	13
Electric Multi Braisers - 2/1 GN - Freestanding - H 700 mm	13
Electric Multi Braisers - 1/1 GN - Freestanding - H 800 mm	14
Electric Multi Braisers - 2/1 GN - Freestanding - H 800 mm	14

Electric Pasta Cookers - Freestanding - H 700 mm	14
Electric Pasta Cookers - Freestanding - H 800 mm	14
Electric Deep Fat Fryers - Freestanding - H 700 mm	15
Electric Deep Fat Fryers - Freestanding - H 800 mm	15
Electric Chip Scuttles	15
Mixing Tap Units - Freestanding - H 700 mm	15
Mixing Tap Units - Freestanding - H 800 mm	16
Mixing Tap Units - Freestanding - Automatic Water Refilling	16
Closed Work Tops - 100 to 300 mm	16
Closed Work Tops - 400 to 600 mm	16
Closed Work Tops - 700 to 900 mm	17
Closed Work Tops - 1000 to 1500 mm	17
Sink Units - Freestanding	17
Closed Bases - H 450 mm	17
Open Bases (GN Conform) - H 450 mm	18
Open Bases - H 450 mm	18
Cupboard Bases (GN Conform) - H 450 mm	18
Passthrough Open Bases (GN Conform) - H 450 mm	18
Passthrough Open Bases - H 450 mm	19
Passthrough Cupboard Bases (GN Conform) - H 450 mm	19
Closed Bases - H 550 mm	19
Open Bases (GN Conform) - H 550 mm	19
Open Bases - H 550 mm	20
Cupboard Bases (GN Conform) - H 550 mm	20
Passthrough Open Bases (GN Conform) - H 550 mm	20
Passthrough Open Bases - H 550 mm	20
Passthrough Cupboard Bases (GN Conform) - H 550 mm	21
Electric Warming Cabinet Bases (GN Conform) - H 450 mm	21
Electric Passthrough Warming Cabinet Bases (GN Conform) - H 450 mm	21
Electric Warming Cabinet Bases (GN Conform) - H 550 mm	21
Electric Passthrough Warming Cabinet Bases (GN Conform) - H 550 mm	22
Holding Cabinet Base (GN Conform) - H 450 mm	22
Holding Cabinet Base (GN Conform) - H 550 mm	22
Electric Static Oven Bases	23
Refrigerated Bases	23

## Electric Solid Tops - 2 Zones



	■ 588000	■ 588001	■ 588002	■ 588003	■ 588004	■ 588005
External dim. - mm						
width	500	500	500	500	500	500
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Electric power - kW	6	6	6	6	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

## Electric Solid Tops - 2 Zones - Freestanding - H 700 mm



	■ 588338	■ 588339	■ 588340	■ 588341	■ 588342	■ 588343
External dim. - mm						
width	500	500	500	500	500	500
depth	800	800	800	800	800	800
height	700	700	700	700	700	700
Electric power - kW	6	6	6	6	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

## Electric Solid Tops - 2 Zones - Freestanding - H 800 mm



	■ 588350	■ 588351	■ 588352	■ 588353	■ 588354	■ 588355
External dim. - mm						
width	500	500	500	500	500	500
depth	800	800	800	800	800	800
height	800	800	800	800	800	800
Electric power - kW	6	6	6	6	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

## Electric Solid Tops - 4 Zones



	■ 588006	■ 588007	■ 588008	■ 588009	■ 588010	■ 588011
External dim. - mm						
width	800	800	800	800	800	800
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Electric power - kW	12	12	12	12	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

### Electric Solid Tops - 4 Zones - Freestanding - H 700 mm



	■ 588344	■ 588345	■ 588346	■ 588347	■ 588348	■ 588349
External dim. - mm						
width	800	800	800	800	800	800
depth	800	800	800	800	800	800
height	700	700	700	700	700	700
Electric power - kW	12	12	12	12	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

### Electric Solid Tops - 4 Zones - Freestanding - H 800 mm



	■ 588356	■ 588357	■ 588358	■ 588359	■ 588360	■ 588361
External dim. - mm						
width	800	800	800	800	800	800
depth	800	800	800	800	800	800
height	800	800	800	800	800	800
Electric power - kW	12	12	12	12	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

### Infrared Tops - 2 and 4 Zones



	■ 588012	■ 588013	■ 588014	■ 588015	■ 588016	■ 588017
External dim. - mm						
width	400	400	400	800	800	800
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Electric power - kW	8	8	8	16	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Zones	2	2	2	4	4	4

### Induction Tops - 2 Zones



	■ 588019	■ 588020	■ 588021
External dim. - mm			
width	400	400	400
depth	800	800	800
height	250	250	250
Electric power - kW	10	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	2	2	2

## Induction Tops - 4 Zones



	■ 588022	■ 588023	■ 588024
External dim. - mm			
width	800	800	800
depth	800	800	800
height	250	250	250
Electric power - kW	20	20	20
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Zones	4	4	4

## Induction Woks



	■ 588025	■ 588026
External dim. - mm		
width	500	500
depth	800	800
height	250	250
Electric power - kW	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
Zones	1	1
Wok	1	1

## Gas Burner Tops - 2 Burners



	■ 588036	■ 588037	■ 588038
External dim. - mm			
width	400	400	400
depth	800	800	800
height	250	250	250
Gas Power - kW	14	14	14
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	2	2	2

## Gas Burner Tops - 4 and 6 Burners



	■ 588039	■ 588040	■ 588041	■ 588042	■ 588043	■ 588044
External dim. - mm						
width	800	800	800	1200	1200	1200
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Gas Power - kW	28	28	28	42	42	42
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Burners	4	4	4	6	6	6



**Gas Burner Tops - 2 Burners - Ecoflam**



	■ 588047	■ 588048	■ 588049
External dim. - mm			
width	400	400	400
depth	800	800	800
height	250	250	250
Gas Power - kW	14	14	14
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	2	2	2
Ecoflam	•	•	•

**Gas Burner Tops - 4 and 6 Burners - Ecoflam**



	■ 588050	■ 588051	■ 588052	■ 588053	■ 588054	■ 588055
External dim. - mm						
width	800	800	800	1200	1200	1200
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Gas Power - kW	28	28	28	42	42	42
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Burners	4	4	4	6	6	6
Ecoflam	•	•	•	•	•	•

**Electric Fry Tops - Smooth Chrome Plate**



	■ 588056	■ 588057	■ 588058	■ 588059
External dim. - mm				
width	400	400	800	800
depth	800	800	800	800
height	250	250	250	250
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

**Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 700 mm**



	■ 588362	■ 588363	■ 588364	■ 588365
External dim. - mm				
width	400	400	800	800
depth	800	800	800	800
height	700	700	700	700
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 800 mm



	■ 588370	■ 588371	■ 588372	■ 588373
External dim. - mm				
width	400	400	800	800
depth	800	800	800	800
height	800	800	800	800
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Electric Fry Tops - Ribbed Chrome Plate



	■ 588064	■ 588065	■ 588066	■ 588067
External dim. - mm				
width	400	400	800	800
depth	800	800	800	800
height	250	250	250	250
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 700 mm



	■ 588366	■ 588367	■ 588368	■ 588369
External dim. - mm				
width	400	400	800	800
depth	800	800	800	800
height	700	700	700	700
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 800 mm



	■ 588374	■ 588375	■ 588376	■ 588408
External dim. - mm				
width	400	400	800	800
depth	800	800	800	800
height	800	800	800	800
Electric power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

**Electric Fry Tops - Smooth and Ribbed Chrome Plate**



	■ 588409	■ 588410
External dim. - mm		
width	800	800
depth	800	800
height	250	250
Electric power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

**Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 700 mm**



	■ 588404	■ 588405
External dim. - mm		
width	800	800
depth	800	800
height	700	700
Electric power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

**Electric Fry Tops - Smooth and Ribbed Chrome Plate - Freestanding - H 800 mm**



	■ 588406	■ 588407
External dim. - mm		
width	800	800
depth	800	800
height	800	800
Electric power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

**Electric Free-cooking Tops**



	■ 588322	■ 588323	■ 588324	■ 588325
External dim. - mm				
width	500	500	800	800
depth	800	800	800	800
height	250	250	250	250
Electric power - kW	6	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Electric Free-cooking Tops - Freestanding - H 700 mm



	■ 588378	■ 588379	■ 588380	■ 588381
External dim. - mm				
width	500	500	800	800
depth	800	800	800	800
height	700	700	700	700
Electric power - kW	6	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Electric Free-cooking Tops - Freestanding - H 800 mm



	■ 588382	■ 588383	■ 588384	■ 588385
External dim. - mm				
width	500	500	800	800
depth	800	800	800	800
height	800	800	800	800
Electric power - kW	6	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Electric Bain Marie Tops



	■ 588086	■ 588087	■ 588400	■ 588401	■ 588402	■ 588403
External dim. - mm						
width	400	400	500	500	500	500
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Electric power - kW	1.5	1.5	1.5	1.5	1.5	1.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Mixing tap position	rear	rear	left	left	right	right

### Electric Bain Marie Tops



	■ 588088	■ 588089
External dim. - mm		
width	800	800
depth	800	800
height	250	250
Electric power - kW	3	3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
Mixing tap position	rear	rear

### Electric Aquacookers - Freestanding - H 700 mm



	■ 588090	■ 588091
External dim. - mm		
width	400	400
depth	800	800
height	700	700
Electric power - kW	7.5	7.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
El. control	•	•

### Electric Aquacookers - Freestanding - H 800 mm



	■ 588253	■ 588254
External dim. - mm		
width	400	400
depth	800	800
height	800	800
Electric power - kW	7.5	7.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
El. control	•	•

### Electric Multi Braisers - 1/1 GN - Freestanding - H 700 mm



	■ 588183	■ 588184
External dim. - mm		
width	400	400
depth	800	800
height	700	700
Electric power - kW	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

### Electric Multi Braisers - 2/1 GN - Freestanding - H 700 mm



	■ 588189	■ 588190
External dim. - mm		
width	800	800
depth	800	800
height	700	700
Electric power - kW	10.2	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

### Electric Multi Braisers - 1/1 GN - Freestanding - H 800 mm



	■ 588277	■ 588278
External dim. - mm		
width	400	400
depth	800	800
height	800	800
Electric power - kW	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

### Electric Multi Braisers - 2/1 GN - Freestanding - H 800 mm



	■ 588283	■ 588284
External dim. - mm		
width	800	800
depth	800	800
height	800	800
Electric power - kW	10.2	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

### Electric Pasta Cookers - Freestanding - H 700 mm



	■ 588203	■ 588204	■ 588205	■ 588206
External dim. - mm				
width	400	400	400	400
depth	800	800	800	800
height	700	700	700	700
Electric power - kW	5	5	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	5x2	5x2	20	20

### Electric Pasta Cookers - Freestanding - H 800 mm



	■ 588289	■ 588290	■ 588291	■ 588292
External dim. - mm				
width	400	400	400	400
depth	800	800	800	800
height	800	800	800	800
Electric power - kW	5	5	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	5x2	5x2	20	20

### Electric Deep Fat Fryers - Freestanding - H 700 mm



	■ 588209	■ 588210	■ 588211	■ 588212	■ 588328	■ 588329
External dim. - mm						
width	400	400	400	400	400	400
depth	800	800	800	800	800	800
height	700	700	700	700	700	700
Electric power - kW	5.4	5.4	12	12	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Tank capacity - lt	7	7	5x2	5x2	14	14

### Electric Deep Fat Fryers - Freestanding - H 800 mm



	■ 588295	■ 588296	■ 588297	■ 588298	■ 588330	■ 588331
External dim. - mm						
width	400	400	400	400	400	400
depth	800	800	800	800	800	800
height	800	800	800	800	800	800
Electric power - kW	5.4	5.4	12	12	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Tank capacity - lt	7	7	5x2	5x2	14	14

### Electric Chip Scuttles



	■ 588094	■ 588095
External dim. - mm		
width	400	400
depth	800	800
height	230	230
Electric power - kW	1	1
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

### Mixing Tap Units - Freestanding - H 700 mm



	■ 588386	■ 588387	■ 588388	■ 588389
External dim. - mm				
width	200	200	200	200
depth	800	800	800	800
height	700	700	700	700
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Lever	•	•		
Knobs			•	•

### Mixing Tap Units - Freestanding - H 800 mm



	■ 588390	■ 588391	■ 588392	■ 588393
External dim. - mm				
width	200	200	200	200
depth	800	800	800	800
height	800	800	800	800
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Lever	•	•		
Knobs			•	•

### Mixing Tap Units - Freestanding - Automatic Water Refilling



	■ 588172	■ 588173	■ 588266	■ 588267
External dim. - mm				
width	200	200	200	200
depth	800	800	800	800
height	700	700	800	800
Electric power - kW	0.1	0.1	0.1	0.1
Electrical connection	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz	230V 1N 50Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

### Closed Work Tops - 100 to 300 mm



	■ 588102	■ 588103	■ 588104	■ 588105	■ 588106	■ 588107
External dim. - mm						
width	100	100	200	200	300	300
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

### Closed Work Tops - 400 to 600 mm



	■ 588108	■ 588109	■ 588110	■ 588111	■ 588112	■ 588113
External dim. - mm						
width	400	400	500	500	600	600
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•



**Closed Work Tops - 700 to 900 mm**



	■ 588114	■ 588115	■ 588116	■ 588117	■ 588118	■ 588119
External dim. - mm						
width	700	700	800	800	900	900
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

**Closed Work Tops - 1000 to 1500 mm**



	■ 588120	■ 588121	■ 588122	■ 588123	■ 588124	■ 588125
External dim. - mm						
width	1000	1000	1200	1200	1500	1500
depth	800	800	800	800	800	800
height	250	250	250	250	250	250
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•

**Sink Units - Freestanding**



	■ 588213	■ 588214	■ 588299	■ 588300
External dim. - mm				
width	400	400	400	400
depth	800	800	800	800
height	700	700	800	800
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

**Closed Bases - H 450 mm**



	■ 588394	■ 588396	■ 588398
External dim. - mm			
width	100	200	300
depth	800	800	800
height	450	450	450

### Open Bases (GN Conform) - H 450 mm



	■ 588126	■ 588131	■ 588132	■ 588326	■ 588133
External dim. - mm					
width	400	500	600	700	800
depth	800	800	800	800	800
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN

### Open Bases - H 450 mm



	■ 588127	■ 588128	■ 588129	■ 588130
External dim. - mm				
width	900	1000	1200	1500
depth	800	800	800	800
height	450	450	450	450
Operating side	1-side	1-side	1-side	1-side

### Cupboard Bases (GN Conform) - H 450 mm



	■ 588134	■ 588135	■ 588136	■ 588138	■ 588137
External dim. - mm					
width	400	500	600	800	1000
depth	800	800	800	800	800
height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN
Doors	1	1	1	2	2

### Passthrough Open Bases (GN Conform) - H 450 mm



	■ 588145	■ 588146	■ 588140	■ 588147
External dim. - mm				
width	500	600	700	800
depth	800	800	800	800
height	450	450	450	450
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Passthrough base	•	•	•	•

### Passthrough Open Bases - H 450 mm



	■ 588141	■ 588142	■ 588143	■ 588144
External dim. - mm				
width	900	1000	1200	1500
depth	800	800	800	800
height	450	450	450	450
Operating side	2-side	2-side	2-side	2-side
Passthrough base	•	•	•	•

### Passthrough Cupboard Bases (GN Conform) - H 450 mm



	■ 588148	■ 588149	■ 588153	■ 588151	■ 588152
External dim. - mm					
width	500	600	800	1000	1200
depth	800	800	800	800	800
height	450	450	450	450	450
Operating side	2-side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN	GN
Doors	2	2	4	4	4
Passthrough base	•	•	•	•	•

### Closed Bases - H 550 mm



	■ 588395	■ 588397	■ 588399
External dim. - mm			
width	100	200	300
depth	800	800	800
height	550	550	550

### Open Bases (GN Conform) - H 550 mm



	■ 588215	■ 588220	■ 588221	■ 588327	■ 588222
External dim. - mm					
width	400	500	600	700	800
depth	800	800	800	800	800
height	550	550	550	550	550
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN

## Open Bases - H 550 mm



	■ 588216	■ 588217	■ 588218	■ 588219
External dim. - mm				
width	900	1000	1200	1500
depth	800	800	800	800
height	550	550	550	550
Operating side	1-side	1-side	1-side	1-side

## Cupboard Bases (GN Conform) - H 550 mm



	■ 588223	■ 588224	■ 588225	■ 588227	■ 588226
External dim. - mm					
width	400	500	600	800	1000
depth	800	800	800	800	800
height	550	550	550	550	550
Operating side	1-side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN	GN
Doors	1	1	1	2	2

## Passthrough Open Bases (GN Conform) - H 550 mm



	■ 588234	■ 588235	■ 588229	■ 588236
External dim. - mm				
width	500	600	700	800
depth	800	800	800	800
height	550	550	550	550
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Passthrough base	•	•	•	•

## Passthrough Open Bases - H 550 mm



	■ 588230	■ 588231	■ 588232	■ 588233
External dim. - mm				
width	900	1000	1200	1500
depth	800	800	800	800
height	550	550	550	550
Operating side	2-side	2-side	2-side	2-side
Passthrough base	•	•	•	•

### Passthrough Cupboard Bases (GN Conform) - H 550 mm



	■ 588237	■ 588238	■ 588242	■ 588240	■ 588241
External dim. - mm					
width	500	600	800	1000	1200
depth	800	800	800	800	800
height	550	550	550	550	550
Operating side	2-side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN	GN
Doors	2	2	4	4	4
Passthrough base	•	•	•	•	•

### Electric Warming Cabinet Bases (GN Conform) - H 450 mm



	■ 588305	■ 588306	■ 588307	■ 588308
External dim. - mm				
width	500	600	800	1000
depth	800	800	800	800
height	450	450	450	450
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN
Doors	1	1	2	2

### Electric Passthrough Warming Cabinet Bases (GN Conform) - H 450 mm



	■ 588309	■ 588310	■ 588311	■ 588312
External dim. - mm				
width	500	600	800	1000
depth	800	800	800	800
height	450	450	450	450
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Doors	2	2	4	4
Passthrough base	•	•	•	•

### Electric Warming Cabinet Bases (GN Conform) - H 550 mm



	■ 588313	■ 588314	■ 588315	■ 588316
External dim. - mm				
width	500	600	800	1000
depth	800	800	800	800
height	550	550	550	550
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN	GN	GN	GN
Doors	1	1	2	2

### Electric Passthrough Warming Cabinet Bases (GN Conform) - H 550 mm



	■ 588317	■ 588318	■ 588319	■ 588320
External dim. - mm				
width	500	600	800	1000
depth	800	800	800	800
height	550	550	550	550
Electric power - kW	2	2	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	2-side	2-side	2-side	2-side
Capacity	GN	GN	GN	GN
Doors	2	2	4	4
Passthrough base	•	•	•	•

### Holding Cabinet Base (GN Conform) - H 450 mm



	■ 588301
External dim. - mm	
width	800
depth	800
height	450
Electric power - kW	1
Electrical connection	220V 1N 50Hz
Operating side	1-side
Drawers (2)	•

### Holding Cabinet Base (GN Conform) - H 550 mm



	■ 588303
External dim. - mm	
width	800
depth	800
height	550
Electric power - kW	1
Electrical connection	220V 1N 50Hz
Operating side	1-side
Drawers (2)	•

### Electric Static Oven Bases



	■ 588157	■ 588158	■ 588247	■ 588248
External dim. - mm				
width	800	800	800	800
depth	800	800	800	800
height	450	450	550	550
Electric power - kW	5	5	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Passthrough oven		•		•

### Refrigerated Bases



	■ 588249	■ 588250
External dim. - mm		
width	1000	1200
depth	800	800
height	550	550
Electric power - kW	0.5	0.5
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz
Operating side	1-side	1-side

## Excellence with the environment in mind

Electrolux Professional solutions perfectly match the customers' needs, including the areas of reliability, cost efficiency and sustainability. The products are the best in terms of quality - durability with low running costs. Some installations have been running for more than 40 years!

- All Electrolux Professional factories are ISO 14001-certified
- All Electrolux Professional solutions are designed for low water, energy and detergent consumption, and for low emissions into the environment
- All Electrolux Professional solutions are the best-in-class in terms of quality, for a long life cycle with the lowest life cycle costs. There are solutions still running after 40 years
- All Electrolux Professional solutions are ROHS and REACH-compliant and over 95% recyclable
- All Electrolux Professional solutions are 100% quality tested and all of the functions are singularly checked by expert technicians
- In the last five years, more than 70% of Electrolux Professional solutions have been updated with features that are always designed with the needs of customers and environmental considerations in mind
- Electrolux Professional sustains a specific energy saving program to reduce the energy consumption of its production plants



*Thinking of you*  
**Electrolux**