

Tabel-Top-Model EST 40 T

Vacuum-Packing-Machines

LC and LS Features

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealing bar, counter bar, hinges
- Soft Air reventilation of the chamber
- Acrylic glas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

Additional LS Features

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



Control panel LC



EST 40 TLS

Technical Data		EST 40 T
■ Chamber size inside	height depth width	200 mm 470 (570*) mm 470 mm
■ External dimensions	height depth width	450 mm 580 mm 535 mm
■ Weight		85 kg
■ Length of sealing bar		460 mm
■ Packaging performance		1 to 2 / min.
■ Vacuum pump standard		21 m ³ / h
■ Electrical supply standard	LC: 230V / 1 or on request LS: 400V / 3 or on request	
* Chamber extension in the middle at 100 mm depth		
<i>Technical modifications reserved</i>		